

Product datasheet

Specifications



PTE voltage measurement input - for MTZ1/2 - fixed

LV847506

Main

Range	MasterPact
Product or component type	Voltage measurement option
Accessory / separate part category	Trip unit accessory
Range compatibility	Masterpact MasterPact MTZ1 circuit-breaker Masterpact MasterPact MTZ2 circuit-breaker
Trip unit name	MicroLogic

Complementary

[Uc] control circuit voltage	100 V AC 50/60 Hz minimum primary circuit 100 V AC 50/60 Hz minimum secondary circuit 690 V AC 50/60 Hz maximum secondary circuit 1250 V AC 50/60 Hz maximum primary circuit
Mounting mode	Fixed

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.5 cm
Package 1 Width	22.0 cm
Package 1 Length	23.0 cm
Package 1 Weight	193.0 g

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins