

Product data sheet

Specifications



voltage release Compact MX - 110..130 V AC 50/60Hz

29386

⚠ Discontinued

Main

Range	ComPact
Range of Product	NS400...630 DC NR100...250 NS100...250 NS400...630 NB400...600 NSJ400...600 NR400...630 NS100...250 DC NS125E NSF150...250
Device short name	MX
Product or Component Type	Voltage release
Device Application	Control
Voltage release type	Shunt trip release
[Uc] control circuit voltage	110...130 V AC 50/60 Hz
Range compatibility	ComPact ComPact NS ComPact Compact NB ComPact Compact NR ComPact Compact NSF ComPact Compact NSJ

Complementary

Operating threshold	0.7...1.1 x Un
Control signal type	Impulse Maintained
Impulse duration	>= 20 ms
Auxiliary connection terminal	screw terminal 0...0.002 in² (0...1.5 mm²)

Ordering and shipping details

Category	01103-H,J,COMPACT NS UL/IEC CIRCUIT BREAKER ACCESSORIES
Discount Schedule	DE2
GTIN	00785901109976
Returnability	No
Country of origin	FR

Contractual warranty

Warranty (in months)	18
----------------------	----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.