

Product data sheet

Specifications



Electronic motor relay expansion cable RJ45 CONNECTOR 0,1M

LTMT9RJ401

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
Product or Component Type	Cable
Accessory / separate part category	Connection accessory
Range compatibility	TeSys TeSys Tera motor controller

Complementary

Cable length	0.49 ft (0.15 m)
Electrical circuit type	Communication
Wire insulation material	Rubber
Connections - terminals	2 x plug-in connector RJ45
Quantity per Set	1 set

Ordering and shipping details

Category	US10I1222335
Discount Schedule	0I12
GTIN	3606482233737
Returnability	Yes
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.2 in (5.7 cm)
Package 1 Width	3.9 in (10 cm)
Package 1 Length	4.3 in (11 cm)
Package weight(Lbs)	3.2 oz (90 g)
Unit Type of Package 2	S01
Number of Units in Package 2	12
Package 2 Height	5.9 in (15 cm)
Package 2 Width	5.9 in (15 cm)
Package 2 Length	15.7 in (40 cm)
Package 2 Weight	3.353 lb(US) (1.521 kg)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 3	P06
Number of Units in Package 3	576
Package 3 Height	413.4 in (1050 cm)
Package 3 Width	38.6 in (98 cm)
Package 3 Length	46.5 in (118 cm)
Package 3 Weight	140.74 lb(US) (63.84 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	0.3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint of the manufacturing phase [A1 to A3]	0.2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration
Halogen content performance	Halogen free plastic parts product
PVC free	Yes
Silicon free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	46
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.