

Product datasheet

Specifications



Circuit breaker frame, adapt EasyPact NW, 3 Poles, 1600A, fixed

ENW13213

Main

Range of product	EasyPact NW
Range	EasyPact
Product or component type	Circuit breaker
Device short name	ENW16C
Device application	Distribution
Poles description	3P
Protected poles description	3P 3d
Network type	AC
Breaking capacity code	C
Suitability for isolation	Yes conforming to IEC 60947-2
Utilisation category	Category B

Complementary

Network frequency	50/60 Hz
Mounting mode	Fixed
Mounting support	Rail Base plate
Connection position	Horizontal Vertical
Location of connection	Rear
[In] rated current	1600 A at 40 °C
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	12 kV conforming to IEC 60947-2
[Icm] rated short-circuit making capacity	75 kA (Icm) at 220...440 V AC 50/60 Hz conforming to IEC 60947-2
[Ue] rated operational voltage	440 V AC 50/60 Hz conforming to IEC 60947-2
Breaking capacity	66 kA Icu at 220...440 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service breaking capacity	55 kA (Ics) at 220...440 V AC 50/60 Hz conforming to IEC 60947-2
Circuit breaker CT rating	1600 A
Mechanical durability	20000 cycles (with maintenance) conforming to IEC 60947-2 10000 cycles (without maintenance) conforming to IEC 60947-2
Electrical durability	Category B: 5000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2
Connection pitch	70 mm without spreader

Excluding VAT, FCA Jabal Ali & amp; are subject to change – check with your local distributor.

Contact position indicator	Yes
[Icw] rated short-time withstand current	50 kA (1 s) at 220...440 V AC 50/60 Hz conforming to IEC 60947-2
Maximum breaking time	35 ms
Maximum closing response time	70 ms
Height	301 mm
Width	276 mm
Depth	196 mm
Product weight	14 kg

Environment

Standards	IEC 60947-2
Product certifications	EAC IEC
IP degree of protection	IP30
Pollution degree	3 conforming to IEC 60664-1
Ambient air temperature for operation	-5...70 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.1 cm
Package 1 Width	27.6 cm
Package 1 Length	29.6 cm
Package 1 Weight	14 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	4 166 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	93 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	23 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.9 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	4 012 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	37 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards
SCIP Number	3f2d539a-6ab5-46aa-8603-9354f4ae3294
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	68
End of life manual availability	End of Life Information
Take-back	No

Offer Marketing Illustration

Product benefits / Features

EasyPact NW



The central image shows a Schneider EasyPact NW circuit breaker unit, a compact, black metal enclosure with a green status bar on top. It is surrounded by six feature callouts:

- NFC connectivity**: Represented by a smartphone icon with a signal wave, indicating wireless communication capabilities.
- Colour-coded health status bar**: Accompanied by a hand icon, describing the visual monitoring system for proactive actions.
- Simpler commissioning**: Shown with a checkmark icon, highlighting the ease of setup through EPIC and mobile EPD.
- Innovative front-end retrofit capability**: Marked with a magnifying glass icon, noting that upgrades can be completed in just 5 minutes without a shutdown.
- Detailed event logs**: Indicated by a calendar icon, providing easy access to trip event records for rapid fault diagnosis.
- Compact frame**: Represented by a bolt icon, emphasizing the high breaking capacity (up to 66 kA) achieved in a smaller footprint.

Technical Illustration

Assembly's dimensions

