



lower part of enclosure for 3RW55/52 frame size 2 and 3

product designation	Enclosure lower part
product type designation	3RW59
manufacturer's article number of soft starter	<ul style="list-style-type: none"> <li>• 3RW511, 3RW512, 3RW513</li> <li>• 3RW522, 3RW523</li> <li>• 3RW552.-.HA..., 3RW553.-.HA..</li> </ul>

**General technical data**

Substance Prohibitance (Date)	02/15/2018
Net Weight	0.92 kg



**Ambient conditions**

ambient temperature during storage	-40 ... +80 °C
------------------------------------	----------------

**Approvals Certificates**

General Product Approval	EMV	For use in hazardous locations	Test Certificates
   		<a href="#">Miscellaneous</a>	<a href="#">Type Test Certificates/Test Report</a>

**Maritime application** other

   		<a href="#">Confirmation</a>
---	---	------------------------------

**Environment**

[Environmental Confirmations](#)

**Further information**

- Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage  
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (Catalogs, Brochures,...)  
<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5953-0GB00>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5953-0GB00>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5953-0GB00&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5953-0GB00&lang=en)

**Cax online generator**

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5953-0GB00>

**Characteristic curves**

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

**Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current**

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5953-0GB00/char>

**Characteristic: Installation altitude**

[https://www.automation.siemens.com/bilddb/index.aspx?gridview=view2&objkey=G\\_NSB0\\_XX\\_01704&showdetail=true&view=Search](https://www.automation.siemens.com/bilddb/index.aspx?gridview=view2&objkey=G_NSB0_XX_01704&showdetail=true&view=Search)

**Simulation Tool for Soft Starters (STS)**

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

---

last modified:

4/2/2025 

