

Article No. : 1FK7062-2AF71-1BA2

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :



Figure similar

Engineering data	
Rated speed (100 K)	3,000 rpm
Number of poles	8
Rated torque (100 K)	6.0 Nm
Rated current	4.0 A
Static torque (60 K)	7.10 Nm
Static torque (100 K)	8.50 Nm
Stall current (60 K)	4.30 A
Stall current (100 K)	5.30 A
Moment of inertia	11.200 kgcm ²
Efficiency	91.0 %

Physical constants	
Torque constant	1.60 Nm/A
Voltage constant at 20° C	102.5 V/1000*min ⁻¹
Winding resistance at 20° C	1.15 Ω
Rotating field inductance	14.6 mH
Electrical time constant	12.80 ms
Mechanical time constant	1.49 ms
Thermal time constant	35 min
Shaft torsional stiffness	37,000 Nm/rad
Net weight of the motor	9.1 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	63
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP65 and DE flange IP67
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	without holding brake
Shaft end	Feather key
Encoder system	Encoder AS24DQI: absolute encoder single-turn 24 bits

Optimum operating point	
Optimum speed	3,000 rpm
Optimum power	1.9 kW

Limiting data	
Max. permissible speed (mech.)	7,200 rpm
Max. permissible speed (inverter)	5,600 rpm
Maximum torque	26.0 Nm
Maximum current	19.2 A

Recommended Motor Module	
Rated inverter current	5 A
Maximum inverter current	15 A
Maximum torque	22.10 Nm