


Product data sheet

Specifications



bar-mounted contactor - TeSys LC1-BR -1P- AC-1 1000 V 2750 A - coil 240 VAC

LC1BR31U22

⚠ Discontinued on: Jul 12, 2021

⚠ Discontinued

Main

Range	TeSys
Product name	TeSys B
Product or Component Type	Contactors
Device short name	LC1BR
Contactors application	Motor-heating-lighting
Utilisation category	AC-1
Control circuit type	AC
Coil type	Standard
Poles description	1P
Pole contact composition	1 NO
[Ie] rated operational current	2750 A (at <104 °F (40 °C)) AC AC-1 for power circuit
Auxiliary contact composition	2 NO + 2 NC
[Uc] control circuit voltage	240 V AC 50...400 Hz

Complementary

Protective cover	With
Auxiliary contacts type	Instantaneous 2 NO + 2 NC
Control circuit voltage limits	Operational: 0.85...1.1 Uc Drop-out: 0.4...0.5 Uc
[Ui] rated insulation voltage	1000 V - power circuit IEC 60158-1 1000 V - power circuit IEC 60947-4 1500 V - power circuit VDE 0110 group C
Connections - terminals	Power circuit bars 4 x 100 x 5 mm
Tightening torque	Power circuit 309.8 lbf.in (35 N.m) bars
[Ue] rated operational voltage	Power circuit <= 1000 V AC 50/60 Hz
[Ith] conventional free air thermal current	2750 A (at 104 °F (40 °C)) for power circuit
Irms rated making capacity	18000 A at 1000 V AC for power circuit conforming to IEC 60158-1 18000 A at 1000 V AC for power circuit conforming to IEC 60947-4
Rated breaking capacity	11000 A at 660...690 V for power circuit conforming to IEC 60158-1 11000 A at 660...690 V for power circuit conforming to IEC 60947-4 15000 A at 500 V for power circuit conforming to IEC 60158-1 15000 A at 500 V for power circuit conforming to IEC 60947-4 18000 A at 440 V for power circuit conforming to IEC 60158-1 18000 A at 440 V for power circuit conforming to IEC 60947-4 6000 A at 1000 V for power circuit conforming to IEC 60158-1 6000 A at 1000 V for power circuit conforming to IEC 60947-4

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Associated fuse rating	2000 A aM at <= 440 V for power circuit 2400 A gI at <= 440 V for power circuit
Average impedance	0.09 mOhm - lth 2750 A 50 Hz for power circuit
Power dissipation per pole	680 W AC-1 - lth 2750 A
Inrush power in VA	620 VA
Hold-in power consumption in VA	10 VA
Operating time	100...150 ms closing 20...40 ms opening
Mechanical durability	1200000 cycles
Maximum operating rate	120 cyc/h 131 °F (55 °C)
Rated operational power in VA	2000 VA 110...127 V AC-1 1000000 cycles - control circuit 3500 VA 500 V AC-1 1000000 cycles - control circuit 4000 VA 220 V AC-1 1000000 cycles - control circuit 4000 VA 380 V AC-1 1000000 cycles - control circuit 4000 VA 415...440 V AC-1 1000000 cycles - control circuit
Rated operational power in W	200 W 500 V AC 1000000 cycles - control circuit 230 W 440 V AC 1000000 cycles - control circuit 250 W 110 V AC 1000000 cycles - control circuit 250 W 220 V AC 1000000 cycles - control circuit
Height	21.9 in (555 mm)
Width	18.7 in (475 mm)
Depth	18.7 in (475 mm)
Net Weight	114.6 lb(US) (52 kg)

Environment

Standards	NF C 63-110 VDE 0660 IEC 60158-1 IEC 60947-4 BS 5424
Product Certifications	RINA BV CSA
Protective treatment	TC TH
Ambient Air Temperature for Operation	23...131 °F (-5...55 °C)
Ambient Air Temperature for Storage	-76...176 °F (-60...80 °C)
Operating altitude	9842.52 ft (3000 m) without derating

Ordering and shipping details

Category	18402-WORLD SERVICE PARTS(CONTROL ACCESS)
Discount Schedule	CP10
GTIN	3606485336923
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	20.5 in (52 cm)

Package 1 Width	22.8 in (58 cm)
Package 1 Length	26.4 in (67 cm)
Package weight(Lbs)	131.2 lb(US) (59.5 kg)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.