



Main

Product or component type	Auxiliary contact
Breaking capacity code	GJL

Complementary

Rated voltage	480 V AC 600 V DC
Line Rated Current	3 A 6 A
Contacts type and composition	1 NO + 1 NC
Marking	A B

Environment

product certifications	CSA UL listed
------------------------	------------------

Offer Sustainability

Not Green Premium product	Not Green Premium product
Will be Compliant on 4Q2016	Will be Compliant on 4Q2016 Will be Compliant on 4Q2016
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
DINP, which is known to the State of California to cause cancer, and	DINP, which is known to the State of California to cause cancer, and
DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm.	DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.