

Product data sheet

Specifications



Auxiliary contact kit, GoPact MTS 630, 2 NO/NC contacts , ON/OFF indication

GMSAUXCK04

Main

Range of product	GoPact MTS
Product or component type	Auxiliary contact
Device application	Monitoring
Range compatibility	GoPact MTS 630
Product compatibility	switch disconnecter 400...630 A
Frame size	4
Signal contacts composition	2 NO/NC for on/off indication

Complementary

Mounting mode	Clip-on
[I _{th}] conventional free air thermal current	10 A
[U _e] rated operational voltage	415 V AC
[I _e] rated operational current	AC-15: 4 A at 415 V AC 50/60 Hz
Minimum load	1 A
Mechanical durability	50000 cycles
Auxiliary connection terminal	Screw terminal

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	3.2 cm
Package 1 Length	12 cm
Package 1 Weight	0.1 kg
Unit Type of Package 2	S02
Number of Units in Package 2	2
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	0.6 kg

Contractual warranty

List Price displayed is VAT EXCLUSIVE.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Take-back	No
-----------	----

Technical Illustration

Assembly's dimensions

