

# Product data sheet

Specifications



## Dimmer, Sedna, rotary, 1000VA, beige

SDN2200947

! To be discontinued on: 31 December 2025

! To be discontinued

### Main

Range of product	Sedna
Product or component type	Dimmer
Device presentation	Mechanism with fixing frame
Device application	Light control
Colour tint	Beige
Kind of terminals	Pillar terminals

### Complementary

Device mounting	Flush
Dimmer control	Rotary push type
Load type	230 V AC halogen lamp: 40...1000 W 230 V AC incandescent lamp: 40...1000 W Low voltage halogen lamp with ferromagnetic transformer: 60...1000 VA Single-phase motor: 60...600 VA
Rated voltage	230 V AC
Protection type	Electronic fuse protection
Main colour tint	Beige
Material	Thermoplastic ABS-UV stabilised
Surface finish	Glossy
Terminal capacity	2 cable(s) 2.5 mm <sup>2</sup>
Wire structure	Flexible Rigid
Wire stripping length	7 mm
Fixing mode	Screws
Height	71 mm
Width	71 mm
Depth	48.25 mm
Depth of visual part	20 mm
Product weight	0.1037 kg
Market segment	Residential Small commercial

## Environment

Standards	EN 60669-2-1
Conformity mark	CE
Product certifications	GOST-R
IP degree of protection	IP20

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.1 cm
Package 1 Width	7.1 cm
Package 1 Length	4.5 cm
Package 1 Weight	103.7 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.1 cm
Package 2 Width	18.5 cm
Package 2 Length	27.5 cm
Package 2 Weight	1.135 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Weight	8.296 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------

## Recommended replacement(s)