

Product datasheet

Specifications



Earth-leakage relay RHUs - 0.03..30 A - 0..5 s - 240 V

LV481001

Main

Range	VigiPacT
Device short name	RHUs
Product or component type	Residual current protection relay
Relay application	Monitoring relay Protection relay
Mounting support	Front panel
Earth-leakage protection class	Type A
Type of setting	Keypad
Residual earth-leakage sensinty adjustment type	Adjustable
Earth-leakage sensitivity	0.03...1 A, adjustable in step of 0.001 A 1...30 A, adjustable in step of 0.1 A
Earth-leakage time delay	Instantaneous for 0.03 A Adjustable 0...4.5 s for 0.03...30 A adjustable in step of 10 ms
Threshold setting	0.015...1 A adjustable in step of 0.001 A pre-alarm 1...30 A adjustable in step of 0.1 A pre-alarm 0.03...1 A adjustable in step of 0.001 A alarm 1...30 A adjustable in step of 0.1 A alarm
Current sensors compatibility	VigiPacT TOA earth leakage current sensor VigiPacT A earth leakage current sensor VigiPacT L earth leakage current sensor
[Ithe] conventional enclosed thermal current	8 A
Minimum load	10 mA at 12 V
[Us] rated supply voltage	220...240 V AC 50/60 Hz 70...110 %
Power consumption in VA	8 VA
Monitored distribution system	1000 V - AC at 50/60 Hz (maximum) 1000 V - AC at 400 Hz (maximum)
Earthing system	TT IT TN-S
[Uimp] rated impulse withstand voltage	8 kV
Reset	Manual reset

Complementary

Test function	Local Remote test
Signal contacts composition	1 C/O alarm fail-safe 1 NO pre-alarm fail-safe

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Type of measurement	Earth fault current internal measurement, range: 20...200 %, accuracy: +/- 20 %
Refresh time	0.5 s
Tamperproof of settings	Protected by access code
Connections - terminals	Alarm circuit: terminal block cable(s) 0.2...2.5 mm² flexible AWG 22...AWG 12 Alarm circuit: terminal block cable(s) 0.2...2.5 mm² rigid AWG 22...AWG 12 Relay test and fault reset: terminal block cable(s) 0.2...2.5 mm² flexible AWG 22...AWG 12 Relay test and fault reset: terminal block cable(s) 0.2...2.5 mm² rigid AWG 22...AWG 12 Sensor: terminal block cable(s) 0.2...2.5 mm² flexible AWG 22...AWG 12 Sensor: terminal block cable(s) 0.2...2.5 mm² rigid AWG 22...AWG 12 Voltage presence: terminal block cable(s) 0.2...2.5 mm² flexible AWG 22...AWG 12 Voltage presence: terminal block cable(s) 0.2...2.5 mm² rigid AWG 22...AWG 12 Power supply: terminal block cable(s) 0.2...2.5 mm² flexible AWG 22...AWG 12 Power supply: terminal block cable(s) 0.2...2.5 mm² rigid AWG 22...AWG 12 Pre alarm: terminal block cable(s) 0.2...2.5 mm² flexible AWG 22...AWG 12 Pre alarm: terminal block cable(s) 0.2...2.5 mm² rigid AWG 22...AWG 12
Wire stripping length	Alarm circuit: 6 mm Relay test and fault reset: 6 mm Sensor: 6 mm Voltage presence: 6 mm Power supply: 6 mm Pre alarm: 6 mm
Tightening torque	Alarm circuit: 0.5 N.m Relay test and fault reset: 0.5 N.m Sensor: 0.5 N.m Voltage presence: 0.5 N.m Power supply: 0.5 N.m Pre alarm: 0.5 N.m
Standards	EN/IEC 60947-2 Annex M EN/IEC 60755
Width	72 mm
Height	72 mm
Depth	117 mm
Cut-out dimensions	68 x 68 mm
Net weight	0.3 kg
IP degree of protection	IP40 front face: conforming to IEC 60529 IP30 other parts: conforming to IEC 60529 IP20 connection: conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Mechanical robustness	Vibrations 13.2...100 Hz: 0.7 g Vibrations 2...13.2 Hz: +/- 1 mm

Environment

Environmental characteristic	Exposure to damp heat not in service conforming to IEC 60068-2-30 Exposure to damp heat in service conforming to IEC 60068-2-56 Salt mist conforming to IEC 60068-2-52
Overvoltage category	IV
Electrical shock protection class	Class II
Electromagnetic compatibility	Conducted and radiated emissions: , B, conforming to CISPR 11 Conducted radio-frequency immunity test: , 3, conforming to IEC 61000-4-6 Electrostatic discharge immunity test: , 4, conforming to IEC 61000-4-2 High-energy conducted susceptibility: , 4, conforming to IEC 61000-4-5 Low-energy conducted susceptibility: , 4, conforming to IEC 61000-4-4 Radiated susceptibility: , 3, conforming to IEC 61000-4-3
Relative humidity	95 % at 55 °C
Pollution degree	3 conforming to IEC 60664-1

Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	11.0 cm
Package 1 Length	15.5 cm
Package 1 Weight	430.0 g
Unit Type of Package 2	S04
Number of Units in Package 2	24
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	11.086 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	161 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	22 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	138 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.6 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	6b2913b0-ca83-4683-bb4c-744a8bb90c08
Halogen-free status	Halogen free plastic parts product

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	0
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

Assembly's dimensions

