

Product data sheet

Specifications



ASCO 3220 Load Bank

ASCOLBLV3220

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

Voltage Rating	380 V AC 50 Hz
	400 V AC 50 Hz
	415 V AC 50 Hz
	440 V AC 60 Hz
	480 V AC 60 Hz
Capacity Rating	2150 kW
Load Step Resolution	1 kW
Cooling System Rating	14265467.02 Gal/hr(US) (53999.7 m3/h)
Provided Equipment	1 gland plate 3 Cooling fans 2
Enclosure Material	Zintec
Surface Finish	Zinc plated
Color	Gray
Connection Terminals	Terminals inside)
Length	116.5 in (2958 mm)
Width	73.5 in (1868 mm)
Height	88.6 in (2250 mm)
Product Weight	5269.05 lb(US) (2390 kg)

Environment

Ambient Air Temperature	95 °F (35 °C)
Standards	ISO 9001 CE
IP Protection	IP1x IP54

Contractual warranty

Warranty (in months)	18
----------------------	----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

Use Longer



Lifetime extension

Repair **No**