

Product data sheet

Specifications



ASCO 4950 Load Bank

ASCOLBLV4950

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Complementary

Voltage Rating	400 V AC 50 Hz, 3 phase 480 V AC 60 Hz, 3 phase 600 V AC 60 Hz, 3 phase
Capacity Rating	2500 kW 3000 kW 3500 kW 4000 kW
Load Step Resolution	50 kW
Cooling System Rating	29623384.3 Gal/hr(US) (112134.7 m3/h)
Provided Equipment	Switch 3 On-Off LED 2 on LED 1 alarm indication Fuse Cooling fans
Enclosure Material	Aluminium Steel
Surface Finish	Polyester powder
Color	Gray
Connection Terminals	Terminals inside)
Length	166.3 in (4223 mm)
Width	100 in (2540 mm)
Height	141.0 in (3581 mm)
Product Weight	9598.9 lb(US) (4354 kg)

Environment

Ambient Air Temperature	-18...122 °F (-28...50 °C)
Standards	ISO 9001 NEMA

Contractual warranty

Warranty (in months)	18
-----------------------------	----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

Use Longer



Lifetime extension

Repair **No**