

Product datasheet

Specifications



EV charge controller, EcoStruxure EV Charging Expert, 100 charging stations, dynamic charge management

HMIBSCEA53D1EDL

! Discontinued

! Discontinued on: Sep 26, 2025 AD

Main

Range	EcoStruxure EV Charging Expert
Product name	EcoStruxure EV Charging Expert
Product or component type	EV charge controller
Type of installation	Indoor

Complementary

Installed device	Modem 3G/4G (to be ordered separately) Meter device (to be ordered separately)
Range compatibility	EVlink EVlink Smart Wallbox EVlink EVlink parking EVlink EVlink City
Device application	To manage the overall energy allocated to each vehicle
Mounting mode	Wall mount
Mounting support	Rail
Mounting position	Horizontal/vertical
load management	Dynamic
max managed charging stations	100 charging stations
max managed charging points	200 charge points
max nb of zone levels	3
max nb of zones	20
functions selection	With priority charging profile With time-of-use settings
Communication interface	Ethernet RJ45 Cat.6 to connect device to charging station Ethernet RJ45 to connect device to charging station Modem to connect device to central management system
Communication service	Web server for OCPP 1.6 Via Modem
OCPP version	JSON
[Us] rated supply voltage	12...24 V DC
Power consumption in W	16 W
Input type	Energy meter
Electromagnetic compatibility	Conducted and radiated emissions class A conforming to EN 55022
Height	150 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	157 mm
Depth	46 mm
Net weight	1 kg
Standards	EN/IEC 61131-2 EN 55011 EN/IEC 61000-6-4
Product certifications	CE EAC RCM
Targeted country	All
Services	Commercial service plan 0...50 °C

Environment

IP degree of protection	IP40
Ambient air temperature for operation	0...50 °C
Ambient air temperature for storage	-20...60 °C
Operating altitude	0...2000 m
Relative humidity	10...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	22.0 cm
Package 1 Length	32.5 cm
Package 1 Weight	1.412 kg
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	9.732 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	3fe7d895-f8a3-452a-ad75-1d17e7e6e6eb
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Removable battery	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins