

# Product datasheet

Specifications



## undervoltage release MN - 125 V DC - for EZC250, EZCV250

EZEUVR125DC

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

### Main

Range	EasyPact
Range of product	EZC250 EZCV250
Device short name	MN
Product or component type	Voltage release
Device application	Control
Voltage release type	Undervoltage release
[Uc] control circuit voltage	125 V DC
Range compatibility	EasyPact EasyPact EZC

### Complementary

Operating threshold	0.35...0.7 Un opening 0.85 Un closing
---------------------	--

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

EU RoHS Directive

[Compliant](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins