



Harmony GTUX
eXtreme outdoor HMI panels
Displays and Box modules



HMIDT 35X/35XFH



HMIDT 65X/65XFH



HMIDT 75X/75XFH



HMIG 3X/3XFH

Harmony GTUX eXtreme Display modules							
Data entry method	Display size	Resolution (pixels)	Colors	Touch type	Conformal coating Class 3C3	Reference	Weight kg/lb
Via touch screen	7"	800 x 480 (WVGA)	262 K	Single-touch analog resistive	No	HMIDT35X	1.300/2.900
					Yes	HMIDT35XFH	1.300/2.900
	12.1"	1,280 x 800 (WXGA)	262 K	Single-touch analog resistive	No	HMIDT65X	3.200/7.100
					Yes	HMIDT65XFH	3.200/7.100
	15.6"	1,366 x 768 (FWXGA)	262 K	Single-touch analog resistive	No	HMIDT75X	4.800/10.600
					Yes	HMIDT75XFH	4.800/10.600

Harmony GTUX eXtreme Box modules							
Operating system	Number of ports	Application memory capacity (or system card)	Backup memory	Number of Ethernet ports	Conformal coating Class 3C3	Reference	Weight kg/lb
Harmony operating system	2x USB 2.0 (Type A) 1x USB 2.0 (Mini-B) 2x Serial	1x GB SD card	512 KB (NVRAM)	2	No	HMIG3X	0.900/1.980
					Yes	HMIG3XFH	0.900/1.980