

Product datasheet

Specifications

Motors



AC servo motor BDH - 1.5 N.m -
6000 rpm - key shaft - without brake
- IP54

BDH0841H15A2B

EAN Code: 3389118184305

! Discontinued

Main

Product or component type	AC servo motors
Component name	BDH
Continuous stall torque	1.5 N.m for LXM15LD21M3 single phase 2.06 N.m for LXM15LD21M3 3 phases
Peak stall torque	3.14 N.m for LXM15LD21M3 at 230 V single phase 4.78 N.m for LXM15LD21M3 at 230 V 3 phases
Nominal output power	900 W for LXM15LD21M3 at 230 V single phase 950 W for LXM15LD21M3 at 230 V 3 phases
Nominal torque	1.48 N.m for LXM15LD21M3 at 230 V single phase 1.68 N.m for LXM15LD21M3 at 230 V 3 phases
Nominal speed	5500 rpm for LXM15LD21M3 at 230 V 3 phases 6000 rpm for LXM15LD21M3 at 230 V single phase
Maximum mechanical speed	6000 rpm
Product compatibility	LXM15LD21M3 at 230 V 3 phases LXM15LD21M3 at 230 V single phase
Shaft end	Keyed
IP degree of protection	IP54
Encoder type	2-pole resolver
Speed feedback resolution	65536 points/turn
Holding brake	Without
Mounting support	NEMA flange
Electrical connection	Rotatable right-angled connectors
Number of poles	10

Complementary

Range compatibility	Lexium 15
Maximum current Irms	15.84 A
Torque constant	0.37 N.m/A at 120 °C
Back emf constant	23.7 V/krpm at 120 °C
Stator resistance	1.51 Ohm at 20 °C
Stator inductance	5 mH at 20 °C
Stator electrical time constant	3.31 ms at 20 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum radial force Fr	310 N at 6000 rpm
	340 N at 5000 rpm
	370 N at 4000 rpm
	400 N at 3000 rpm
	430 N at 2000 rpm
	460 N at 1000 rpm
Maximum axial force Fa	0.3 x Fr
Net weight	2.44 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No