

Product data sheet

Specifications



Miniature Circuit Breaker, Domae, 25A 1P 230V C-curve 6 Ka

DOM11379

⚠ Discontinued on: 15 Aug 2025

⚠ Discontinued

Main

| | |
|---------------------------|---|
| Device application | Distribution |
| Range | Domae |
| Product or component type | Miniature circuit-breaker |
| Device short name | Domae MCB |
| Poles description | 1P |
| Number of protected poles | 1 |
| [In] rated current | 25 A |
| Network type | AC |
| Curve code | C |
| Breaking capacity | 6000 A at 230/400 V AC 50/60 Hz conforming to IEC 60898-1 |

Complementary

| | |
|--|---|
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | 230/400 V AC 50/60 Hz |
| Contact position indicator | Yes |
| Control type | Toggle |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| Comb busbar and distribution block compatibility | YES |
| Height | 81 mm |
| Width | 18 mm |
| Depth | 78.5 mm |
| Mechanical durability | 10000 cycles |
| Electrical durability | 10000 cycles 230/400 V AC 50/60 Hz conforming to IEC 60898-1 |
| Connections - terminals | Tunnel type terminals1...25 mm ² rigid Tunnel type terminals1...16 mm ² flexible |
| Wire stripping length | AC: 14 mm |
| Tightening torque | 2 N.m |

Environment

| | |
|-----------|------------------------------|
| Standards | SNI 04-6507.1 IEC 60898-1 |
|-----------|------------------------------|

| | |
|---------------------------------------|------------------------------|
| Product certifications | SNI |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Ambient air temperature for operation | -25...60 °C |
| Ambient air temperature for storage | -40...70 °C |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.45 cm |
| Package 1 Width | 1.8 cm |
| Package 1 Length | 8.5 cm |
| Package 1 Weight | 99.0 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 12 |
| Package 2 Height | 8 cm |
| Package 2 Width | 9 cm |
| Package 2 Length | 22 cm |
| Package 2 Weight | 1.241 kg |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 144 |
| Package 3 Height | 30 cm |
| Package 3 Width | 30 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 15388.0 g |

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

| | |
|--|----------------|
| Total lifecycle Carbon footprint | 8 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 0.7 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 0.4 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 7 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 0.3 kg CO2 eq. |

Use Better



Materials and Substances

| | |
|--|---|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant |
| Halogen-free status | Product contains halogen above thresholds |
| PVC free | Yes |

Use Longer



Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again



Repack and remanufacture

| | |
|---------------------------------|--|
| Recyclability potential, in % | 56 |
| End of life manual availability | No need of specific recycling operations |
| Take-back | No |