

# Product data sheet

Specifications



circuit breaker Compact NSXm H  
(70 kA at 415 VAC), 4P 3d, 40 A  
rating TMD trip unit, compression  
lugs and busbar connectors

LV426563

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

## Main

|                                                      |                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                                | ComPact                                                                                                                                                                                                                                                                                                                                                                                 |
| Product name                                         | ComPact NSXm                                                                                                                                                                                                                                                                                                                                                                            |
| Range of product                                     | ComPact NSXm                                                                                                                                                                                                                                                                                                                                                                            |
| Device short name                                    | NSXm 40H                                                                                                                                                                                                                                                                                                                                                                                |
| Product or component type                            | Circuit breaker                                                                                                                                                                                                                                                                                                                                                                         |
| Device application                                   | Protection<br>Distribution                                                                                                                                                                                                                                                                                                                                                              |
| Number of poles                                      | 4P                                                                                                                                                                                                                                                                                                                                                                                      |
| Protected poles description                          | 3D                                                                                                                                                                                                                                                                                                                                                                                      |
| Neutral position                                     | Left                                                                                                                                                                                                                                                                                                                                                                                    |
| [In] rated current                                   | 40 A at 40 °C                                                                                                                                                                                                                                                                                                                                                                           |
| [Ue] rated operational voltage                       | 690 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                       |
| Network type                                         | AC                                                                                                                                                                                                                                                                                                                                                                                      |
| Network frequency                                    | 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                |
| Suitability for isolation                            | Yes conforming to EN/IEC 60947-2                                                                                                                                                                                                                                                                                                                                                        |
| Utilisation category                                 | Category A                                                                                                                                                                                                                                                                                                                                                                              |
| [Icu] rated ultimate short-circuit breaking capacity | 100 kA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2<br>70 kA Icu at 380...415 V AC 50/60 Hz conforming to IEC 60947-2<br>65 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>30 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>22 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA Icu at 660...690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level                                    | H 70 kA 415 V AC                                                                                                                                                                                                                                                                                                                                                                        |
| Trip unit name                                       | TM-D                                                                                                                                                                                                                                                                                                                                                                                    |
| Trip unit technology                                 | Thermal-magnetic                                                                                                                                                                                                                                                                                                                                                                        |
| Trip unit protection functions                       | LI                                                                                                                                                                                                                                                                                                                                                                                      |
| Control type                                         | Toggle                                                                                                                                                                                                                                                                                                                                                                                  |
| Circuit breaker mounting mode                        | By screws<br>Clip-on                                                                                                                                                                                                                                                                                                                                                                    |

## Complementary

|                                        |                   |
|----------------------------------------|-------------------|
| [Ui] rated insulation voltage          | 800 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 8 kV              |

List Price displayed is VAT EXCLUSIVE.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                                                  |                                                                                                                                                                                                                                                                                                                                                                  |
|------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>[Ics] rated service short-circuit breaking capacity</b>       | 100 kA at 220...240 V AC 50/60 Hz conforming to IEC 60947-2<br>70 kA at 380...415 V AC 50/60 Hz conforming to IEC 60947-2<br>65 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>30 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>22 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>2.5 kA at 660...690 V AC 50/60 Hz conforming to IEC 60947-2 |
| <b>Mechanical durability</b>                                     | 20000 cycles                                                                                                                                                                                                                                                                                                                                                     |
| <b>Electrical durability</b>                                     | 10000 cycles at 440 V In<br>20000 cycles at 440 V In/2<br>5000 cycles at 690 V In<br>10000 cycles at 690 V In/2                                                                                                                                                                                                                                                  |
| <b>Mounting support</b>                                          | Plate<br>DIN rail                                                                                                                                                                                                                                                                                                                                                |
| <b>Connection terminals</b>                                      | compression lug/busbar                                                                                                                                                                                                                                                                                                                                           |
| <b>Connection pitch</b>                                          | 35 mm with spreaders<br>27 mm without spreaders                                                                                                                                                                                                                                                                                                                  |
| <b>9 mm pitches</b>                                              | 12 module                                                                                                                                                                                                                                                                                                                                                        |
| <b>Protection type</b>                                           | L : for overload protection (thermal)<br>I : for short-circuit protection (magnetic)                                                                                                                                                                                                                                                                             |
| <b>Trip unit rating</b>                                          | 40 A at 40 °C                                                                                                                                                                                                                                                                                                                                                    |
| <b>Long-time pick-up adjustment type Ir (thermal protection)</b> | Adjustable                                                                                                                                                                                                                                                                                                                                                       |
| <b>[Ir] long-time protection pick-up adjustment range</b>        | 0.7...1 x In                                                                                                                                                                                                                                                                                                                                                     |
| <b>Long-time protection delay adjustment type tr</b>             | Fixed                                                                                                                                                                                                                                                                                                                                                            |
| <b>[Im] magnetic protection pick-up range</b>                    | 600 A                                                                                                                                                                                                                                                                                                                                                            |
| <b>Earth-leakage protection</b>                                  | Without                                                                                                                                                                                                                                                                                                                                                          |
| <b>Number of slots for electrical auxiliaries</b>                | 1 slot(s) for auxiliary switch OF<br>1 slot(s) for alarm switch SD<br>1 slot(s) for voltage release MN or MX                                                                                                                                                                                                                                                     |
| <b>Width (W)</b>                                                 | 108 mm                                                                                                                                                                                                                                                                                                                                                           |
| <b>Height (H)</b>                                                | 137 mm                                                                                                                                                                                                                                                                                                                                                           |
| <b>Depth (D)</b>                                                 | 80 mm                                                                                                                                                                                                                                                                                                                                                            |
| <b>Product weight</b>                                            | 1.42 kg                                                                                                                                                                                                                                                                                                                                                          |
| <b>Colour</b>                                                    | Grey (RAL 7016)                                                                                                                                                                                                                                                                                                                                                  |

## Environment

|                                              |                                                            |
|----------------------------------------------|------------------------------------------------------------|
| <b>Standards</b>                             | EN/IEC 60947                                               |
| <b>Product certifications</b>                | CCC<br>EAC<br>Marine                                       |
| <b>Pollution degree</b>                      | 3 conforming to IEC 60664-1                                |
| <b>IP degree of protection</b>               | IP40 conforming to IEC 60529                               |
| <b>IK degree of protection</b>               | IK07 conforming to IEC 62262                               |
| <b>Ambient air temperature for operation</b> | -25...70 °C                                                |
| <b>Ambient air temperature for storage</b>   | -50...85 °C                                                |
| <b>Relative humidity</b>                     | 0...95 %                                                   |
| <b>Operating altitude</b>                    | 0...2000 m without derating<br>2000...5000 m with derating |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 12 cm     |
| Package 1 Width              | 12 cm     |
| Package 1 Length             | 22 cm     |
| Package 1 Weight             | 1.6 kg    |
| Unit Type of Package 2       | S03       |
| Number of Units in Package 2 | 6         |
| Package 2 Height             | 30 cm     |
| Package 2 Width              | 30 cm     |
| Package 2 Length             | 40 cm     |
| Package 2 Weight             | 10.19 kg  |
| Unit Type of Package 3       | P12       |
| Number of Units in Package 3 | 144       |
| Package 3 Height             | 110 cm    |
| Package 3 Width              | 80 cm     |
| Package 3 Length             | 120 cm    |
| Package 3 Weight             | 254.49 kg |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 150 kg CO2 eq.                                |
| Carbon footprint of the manufacturing phase [A1 to A3] | 11 kg CO2 eq.                                 |
| Carbon footprint of the distribution phase [A4]        | 0.2 kg CO2 eq.                                |
| Carbon footprint of the installation phase [A5]        | 0 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 139 kg CO2 eq.                                |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 0.2 kg CO2 eq.                                |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                   |                                        |
|-------------------|----------------------------------------|
| SCIP Number       | 266401fd-2db7-458f-b0c1-34d573cc83b3   |
| EU RoHS Directive | <a href="#">Compliant By Exemption</a> |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                                 |                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| End of life manual availability | No need of specific recycling operations                                                                                                                                                                        |
| WEEE Label                      |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |