

SIMATIC IPC 477E 19" Touch (1366 x 768); with front USB; 4 USB (back), Ethernet (10/100/1000); Core i5-6442EQ; 3x Gbit Ethernet (IE/PN); 4 GB and NVRAM; 2x RS 232/RS 485; without PCIe; Windows7 Ultimate SP1, 64-bit, MUI (de, en, es, fr, it); Without replaceable mass storage; 320 GB HDD SATA; Without SIMATIC software; 110/230 V AC industrial power supply unit with NAMUR; without power supply cord; - - no BIS certificate for India for 110/230 V AC PS,

General information	
Product type designation	IPC477E
Display	
Design of display	19" TFT touch
Screen diagonal	18.5 in
Resolution (pixels)	
• Horizontal image resolution	1 366 pixel
• Vertical image resolution	768 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Input device	
• Mouse, at front	No
Keyboard	
• Function keys	No
• alphanumeric keyboard	No
Touch operation	
• Design as touch screen	Yes; analog, resistive
Installation type/mounting	
Mounting	For horizontal and vertical mounting
Design	Panel PC, built-in unit
central design	Yes
distributed design	No
Mounting in portrait format possible	Yes
Supply voltage	
Type of supply voltage	100/240 V AC (autorange) 50/60 Hz; optional 24 V DC
Line frequency	
• Rated value 50 Hz	Yes
• Rated value 60 Hz	Yes
Mains buffering	
• Mains/voltage failure stored energy time	20 ms
Power loss	
In full configuration	24 V DC: max. 65 W, PCIe APGB additionally 5 W
Processor	
Processor type	Celeron G3902 (2C/2T, 1.6 GHz, 2 MB Cache); Core i3-6102E (2C/4T, 1.9 GHz, 3 MB Cache); Core i5-6442EQ (4C/4T, 1.9 (2.7) GHz, 6 MB Cache, iAMT); Xeon E3-1505L v5 (4C/8T, 2.0 (2.8) GHz, 8 MB Cache, iAMT)
Chipset	Intel C236 / Intel H110
Graphic	
Graphics controller	Intel HD graphics controller
Drives	
Hard disk	2.5" SATA ≥ 320 GB
SSD	Yes; 128 / 240 / 480 GB
Storage	
Type of memory	DDR4-2400 SO-DIMM
Main memory	4 / 8 / 16 GB, ECC optional
Capacity of main memory, max.	16 Gbyte

Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	512 kbyte; 128 KB can be stored in the buffer time; optional
Hardware configuration	
Slots	
• free slots • Number of PCI slots • Number of compact flash slots	1x PCIe (slot with card retainer), 1x slot for CFAST card 1; Optional 1; CFast
Interfaces	
Number of industrial Ethernet interfaces	3; 3x Ethernet (RJ45)
USB port	4x USB 3.0
Connection for keyboard/mouse	USB / USB
Video interfaces	
• Graphics interface	2x DisplayPort
Industrial Ethernet	
• Industrial Ethernet interface — 100 Mbps — 1000 Mbps	3x Ethernet (RJ45) Yes Yes
Interrupts/diagnostics/status information	
Bus diagnostics	Yes
Integrated Functions	
Monitoring functions	
• Temperature monitoring • Watchdog • Fan • Monitoring function via network	Yes Yes No Optional
EMC	
Interference immunity against discharge of static electricity	
• Interference immunity against discharge of static electricity	±6 kV contact discharge acc. to IEC 61000-4-2; ±8 kV air discharge acc. to IEC 61000-4-2
Interference immunity against high-frequency electromagnetic fields	
• Interference immunity against high frequency radiation	10 V/m, 80 ... 2 000 MHz, 80 % AM acc. to IEC 61000-4-3; 3 V/m, 2 ... 2.7 GHz; 10 V, 10 kHz ... 80 MHz acc. to IEC 61000-4-6
Interference immunity to cable-borne interference	
• Interference immunity on supply cables • Interference immunity on signal cables >30m • Interference immunity on signal cables < 30m	±2 kV acc. to IEC 61000-4-4, burst; ±1 kV acc. to IEC 61000-4-5, surge symmetric; ±2 kV acc. to IEC 61000-4-5, surge asymmetric ±2 kV acc. to IEC 61000-4-5, surge, length > 30 m ±1 kV acc. to IEC 61000-4-4; burst; length < 3 m; ±2 kV acc. to IEC 61000-4-4; burst; length > 3 m
Interference immunity against voltage surge	
• asymmetric interference • symmetric interference	±2 kV acc. to IEC 61000-4-5, surge asymmetric ±1 kV acc. to IEC 61000-4-5, surge symmetric
Interference immunity to magnetic fields	
• Interference immunity to magnetic fields at 50 Hz	100 A/m; to IEC 61000-4-8
Emission of conducted and non-conducted interference	
• Interference emission via line/AC current cables	EN 61000-6-3, EN 61000-6-4, CISPR 22 Class B, FCC Class A
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
• UL 508	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
FCC	Yes
EMC	CE, EN 61000-6-4; CISPR 22:2004 Class A; FCC Class A
Use in hazardous areas	

• ATEX Zone 2 • IECEx Zone 2 • cULus Class I Zone 2, Division 2	Yes; Optional, only with Multitouch																																				
	Yes; Optional, only with Multitouch																																				
	Yes; Optional, only with Multitouch																																				
Marine approval																																					
• Germanischer Lloyd (GL)	Yes																																				
• American Bureau of Shipping (ABS)	Yes																																				
• Bureau Veritas (BV)	Yes																																				
• Det Norske Veritas (DNV)	Yes																																				
• Korean Register of Shipping (KRS)	Yes																																				
• Lloyds Register of Shipping (LRS)	Yes																																				
• Nippon Kaiji Kyokai (Class NK)	Yes																																				
Ambient conditions																																					
Ambient temperature during operation																																					
• min.	0 °C																																				
• max.	45 °C																																				
Ambient temperature during storage/transportation																																					
• min.	-20 °C																																				
• max.	60 °C																																				
Relative humidity																																					
• Relative humidity	Tested according to IEC 60068-2-78, IEC 60068-2-30: 5% to 80% at 25 °C (no condensation)																																				
Vibrations																																					
• Vibration resistance during operation acc. to IEC 60068-2-6	IEC 60068-2-6; 5 Hz to 9 Hz: 3.5 mm; 9 Hz to 500 Hz: 9.8 m/s² (with SSD or CFast); 10 Hz to 58 Hz: 0.0375 mm; 58 Hz to 200 Hz: 4.9 m/s² (hard disk)																																				
Shock testing																																					
• Shock load during operation	IEC 60068-2-27; 150 m/s², 11 ms (without hard disk); 50 m/s², 30 ms (with hard disk)																																				
Operating systems																																					
pre-installed operating system	Windows 7 Ultimate (Multi-Language) 64-bit, Windows Embedded Standard 7 E/P 32-bit / 64-bit, Windows 10																																				
without operating system	Yes; Optional																																				
pre-installed operating system																																					
• Windows 7	Yes; Ultimate 64 bit																																				
• Windows 10 Enterprise	Yes; Windows 10 Enterprise 2016 LTSC, 64 bit, MUI																																				
Software																																					
SIMATIC Software	Optionally with pre-installed SIMATIC WinCC RT Advanced / Software Controller CPU 1500S software bundle																																				
Dimensions																																					
Width of the housing front	483 mm																																				
Height of housing front	337 mm																																				
Mounting cutout, width	465 mm																																				
Mounting cutout, height	319 mm																																				
mounting depth	76 mm																																				
Weights																																					
Weight, approx.	8.4 kg																																				
Classifications																																					
	<table><tr><td></td><td>Version</td><td>Classification</td></tr><tr><td>eClass</td><td>14</td><td>19-20-01-03</td></tr><tr><td>eClass</td><td>12</td><td>19-20-01-03</td></tr><tr><td>eClass</td><td>9.1</td><td>19-20-01-03</td></tr><tr><td>eClass</td><td>9</td><td>19-20-01-03</td></tr><tr><td>eClass</td><td>8</td><td>27-24-23-01</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-23-01</td></tr><tr><td>eClass</td><td>6</td><td>27-24-23-01</td></tr><tr><td>ETIM</td><td>10</td><td>EC001414</td></tr><tr><td>ETIM</td><td>9</td><td>EC001414</td></tr><tr><td>ETIM</td><td>8</td><td>EC001414</td></tr><tr><td>ETIM</td><td>7</td><td>EC001414</td></tr></table>		Version	Classification	eClass	14	19-20-01-03	eClass	12	19-20-01-03	eClass	9.1	19-20-01-03	eClass	9	19-20-01-03	eClass	8	27-24-23-01	eClass	7.1	27-24-23-01	eClass	6	27-24-23-01	ETIM	10	EC001414	ETIM	9	EC001414	ETIM	8	EC001414	ETIM	7	EC001414
	Version	Classification																																			
eClass	14	19-20-01-03																																			
eClass	12	19-20-01-03																																			
eClass	9.1	19-20-01-03																																			
eClass	9	19-20-01-03																																			
eClass	8	27-24-23-01																																			
eClass	7.1	27-24-23-01																																			
eClass	6	27-24-23-01																																			
ETIM	10	EC001414																																			
ETIM	9	EC001414																																			
ETIM	8	EC001414																																			
ETIM	7	EC001414																																			

General Product Approval	Maritime application
--------------------------	----------------------

[Miscellaneous](#)



[BIS CRS](#)

[China RoHS](#)



Maritime application	Dangerous goods
----------------------	-----------------



[Test Summary Report UN 38.3](#)

[Dangerous goods information](#)

last modified:

11/24/2025 