



Catalog No. TLM3220CCUG

Description: 200A 32CT 1P3W 22K IC FLD CONV WGRND BR

UPC No 783164491234

Home > Load Centers > Load Centers

PowerMark Gold convertible load centers arrive as main lug, but have the capability to have a main breaker installed. All ABB load centers are rated up to 60 degree/75 degree centigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TLM3220CCU features space for 32, 1" breakers, 200 A bus ampere rating, a copper bus, a factory installed ground bar, and a combination/flush enclosure.



Representative Image

Descriptors

Category	Load Centers
Grouping	Single Phase - USA

Specifications

Load Center Type	Standard
Input/Output Voltage	120/240V ac
Interrupting Capacity Rating	22
Amperage	200 A
Device type	Main Lug
Enclosure	Indoor
Phase	1 Phase
1" Space	32
1/2" Space	40
Feed	Either
Door	Yes
Circuit Breaker Style	Plug-In
NEMA Rating	NEMA 1
Factory Installed Ground Kit	Yes
Enclosure Type	Indoor, Surface Mount

Classifications

UL/CUL Listing	UL
----------------	----

Dimensions

Width	16
-------	----



Publications

Title	Publication No.	Publication Type
Section 1 BuyLog: Load centers and circuit breakers Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line.	DET1023	Application and Technical

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.