

product type designation

RF210R reader

SIMATIC RF200 reader RF210R; RS422 interface (3964R); IP67, -25 to +70 °C; M18x 71mm; with integrated antenna.



product brand name

SIMATIC RF

Technical Product Detail Page

<https://l.siemens.com/1P6GT2821-1AC10>

suitability for operation

ISO 15693 Transponder (MDS Dxxx), for connecting to communication modules

radio frequencies

operating frequency / rated value

13.56 MHz

range / maximum

20 mm; Range is dependent on transponder type: observe <http://support.automation.siemens.com/WW/view/en/67384964>

protocol / with radio transmission

ISO 15693, ISO 18000-3

transfer rate / with radio transmission / maximum

26.5 kbit/s

product feature / multitag-capable

No

electrical data

transfer rate / at the point-to-point connection / serial / maximum

115.2 kbit/s

transmission time / for user data

- for write access / per byte / typical

0.6 ms

- for read access / per byte / typical

0.6 ms

interfaces

standard for interfaces / for communication

RS422

type of electrical connection

M12, 8-pin

mechanical data

material

Brass, nickel-plated / PBT

color

silver/pastel turquoise

tightening torque / of the screw for securing the equipment / maximum

20 N·m

mounting distance / relating to metal surfaces / recommended / minimum

0 mm

supply voltage, current consumption, power loss

supply voltage / at DC

- rated value

24 V

-

20.4 ... 28.8 V

consumed current / at DC

- at 24 V / typical

0.05 A

ambient conditions

ambient temperature

- during operation

-20 ... +70 °C

- during storage

-25 ... +80 °C

- during transport

-25 ... +80 °C

protection class IP

IP67

shock resistance

EN 60721-3-7 Class 7 M2

shock acceleration	500 m/s ²
vibrational acceleration	200 m/s ²

design, dimensions and weights

height	83 mm
diameter	18 mm
net weight	0.065 kg
fastening method	2 nuts M18 x 1 (included in scope of supply)
wire length	1000 m
<ul style="list-style-type: none"> for RS 422 interface / maximum 	

product features, product functions, product components / general

display version	3-color LED
product feature / silicon-free	Yes

standards, specifications, approvals

certificate of suitability	Radio according to R&TTE guidelines EN300 330 and EN 301489, FCC, cULus
certificate of suitability	
<ul style="list-style-type: none"> IECEX 	No
MTBF	505 a

standards, specifications, approvals / Environmental Product Declaration

Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
<ul style="list-style-type: none"> total during manufacturing during operation after end of life 	43.51 kg 10.7 kg 32.51 kg 0.3 kg

further information / internet links

internet link	
<ul style="list-style-type: none"> to website: Selection guide for cables and connectors to web page: selection aid TIA Selection Tool to web page: RFID country approval to web page: identification and localization systems to web page: SiePortal to website: Image database to website: CAX-Download-Manager to website: Industry Online Support 	https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://www.siemens.com/rfid-approvals https://www.siemens.com/ident https://sieportal.siemens.com/ https://www.automation.siemens.com/bilddb https://www.siemens.com/cax https://support.industry.siemens.com

security information

security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p>
----------------------	---

Approvals / Certificates

General Product Approval



[China RoHS](#)



General Product Approval	EMV	Radio Equipment
--------------------------	-----	-----------------



[China RoHS](#)

[Manufacturer Declaration](#)



[Miscellaneous](#)

Radio Equipment Type Approval Certificate

Environment

[Miscellaneous](#)



last modified:

3/10/2026