

Product datasheet

Specifications



terminal shield - 4 poles - parallel output coupling - for NSX100..250 DC

LV438327

⚠ Discontinued on: 1 Dec 2024

⚠ To be discontinued

Main

Product or component type	Terminal shield
Range compatibility	ComPacT ComPacT NSX DC NSX100 DC ComPacT ComPacT NSX DC NSX160 DC ComPacT ComPacT NSX DC NSX250 DC ComPact Compact NSX100 DC ComPact Compact NSX160 DC ComPact Compact NSX250 DC ComPact INS250 ComPact Compact INV100...250
Accessory / separate part type	Insulation accessories
Poles description	4P
Quantity per set	1 set

Complementary

Output coupling	Parallel
Location of connection	Upstream Downstream
IP degree of protection	IP40 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.500 cm
Package 1 Width	18.000 cm
Package 1 Length	35.000 cm
Package 1 Weight	353.600 g
Unit Type of Package 2	S04
Number of Units in Package 2	9
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	3.882 kg
Unit Type of Package 3	P12
Number of Units in Package 3	36
Package 3 Height	45.000 cm

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	26.730 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	2 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.7 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes
Silicone-free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	2
End of life manual availability	No need of specific recycling operations
Take-back	No