

Product datasheet

Specifications



Multi9 - C68N - MCB - 1P - 63A - B Curve - 230/415V - 6kA

61268

⚠ Discontinued on: 30 Jun 2022

⚠ Discontinued

Main

Range	Multi9
Product or component type	Miniature circuit-breaker
Device application	Distribution
Poles description	1P
Number of protected poles	1
[In] rated current	63 A at 40 °C
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	B
Breaking capacity	6 kA Icu at 240/415 V AC 50/60 Hz conforming to IEC 60898

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	240/415 V AC 50/60 Hz
Magnetic tripping limit	3...5 x In
Limitation class	3
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	75.5 mm
Net weight	0.11 kg
Electrical durability	20000 cycles
Connections - terminals	Tunnel type terminals1...35 mm ² rigid Tunnel type terminals1...25 mm ² flexible

Environment

Tropicalisation	2
Relative humidity	95 % at 55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.3 cm
Package 1 Width	1.8 cm
Package 1 Length	8.5 cm
Package 1 Weight	122 g
Unit Type of Package 2	CAR
Number of Units in Package 2	96
Package 2 Height	40 cm
Package 2 Width	30 cm
Package 2 Length	20 cm
Package 2 Weight	11712 g
Unit Type of Package 3	PAL
Number of Units in Package 3	1536
Package 3 Height	15 cm
Package 3 Width	80 cm
Package 3 Length	60 cm
Package 3 Weight	187392 g



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant](#)

Use Longer



Lifetime extension

Repair

No