

Product datasheet

Specifications



POWER SUPPLY BLOCK UNIVERSAL 250A 4P

04061

⚠ Discontinued on: 23 Sept 2025

⚠ Discontinued

Main

Range	Linergy
Range of product	Linergy
Product or component type	Universal power supply block
Product name	Linergy BW
product name	Prisma Prisma P enclosure Prisma Prisma G enclosure Linergy Linergy BW busbar
Accessory / separate part category	Current distribution accessory
Provided equipment	Without cable
Standards	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma
Product certifications	ASEFA

Complementary

Cubicle-device connection	Linergy BW busbar
Poles description	4P
installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing enclosure - width 850 mm Floor-standing enclosure + duct - width 600 + 300 mm Wall-mounted enclosure + duct - width 600 + 300 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Installed device

ComPact: fixed INS250 - control: direct front rotary handle vertical installation
ComPact: fixed INV250 - control: direct front rotary handle vertical installation
FuPact: fixed ISFT160 - control: fuse carriers handle vertical installation
EasyPact: fixed CVS100...160 without earth leakage protection - control: direct front rotary handle horizontal installation
EasyPact: fixed CVS250 without earth leakage protection - control: direct front rotary handle horizontal installation
EasyPact: fixed CVS100...160 without earth leakage protection - control: direct front rotary handle vertical installation
EasyPact: fixed CVS250 without earth leakage protection - control: direct front rotary handle vertical installation
EasyPact: fixed CVS100...160 without earth leakage protection - control: toggle vertical installation
EasyPact: fixed CVS250 without earth leakage protection - control: toggle vertical installation
ComPact: fixed INV100 - control: direct front rotary handle vertical installation
FuPact: fixed ISFT100N - control: fuse carriers handle vertical installation
ComPact: fixed NSX100...160 without earth leakage protection - control: toggle vertical installation
ComPact: fixed NSX250 without earth leakage protection - control: toggle vertical installation
ComPact: fixed NSX100...160 without earth leakage protection - control: direct front rotary handle vertical installation
ComPact: fixed NSX250 without earth leakage protection - control: direct front rotary handle vertical installation
EasyPact: fixed CVS100...160 with earth leakage protection - control: direct front rotary handle horizontal installation
EasyPact: fixed CVS250 with earth leakage protection - control: direct front rotary handle horizontal installation
EasyPact: fixed CVS100...160 with earth leakage protection - control: direct front rotary handle vertical installation
EasyPact: fixed CVS250 with earth leakage protection - control: direct front rotary handle vertical installation
EasyPact: fixed CVS100...160 with earth leakage protection - control: toggle vertical installation
EasyPact: fixed CVS250 with earth leakage protection - control: toggle vertical installation
ComPact: fixed NSX100...160 with earth leakage protection - control: toggle vertical installation
ComPact: fixed NSX250 with earth leakage protection - control: toggle vertical installation
ComPact: fixed NSX100...160 with earth leakage protection - control: direct front rotary handle vertical installation
ComPact: fixed NSX250 with earth leakage protection - control: direct front rotary handle vertical installation
ComPact: fixed INV200 - control: direct front rotary handle vertical installation
FuPact: fixed INF100...160 - control: extended rotary handle horizontal installation
FuPact: fixed ISFT160 - control: fuse carriers handle horizontal installation
FuPact: fixed ISFT250 - control: fuse carriers handle horizontal installation
FuPact: fixed ISFT250 - control: fuse carriers handle vertical installation
ComPact: fixed INV160 - control: direct front rotary handle vertical installation

[I_e] rated operational current 250 A

[I_n] rated current 250 A

Net weight 0.44 kg

Quantity per set Set of 1

functional unit

650 mm Prisma P cubicle
600 mm Prisma G floor-standing enclosure FuPact INF100...160 fixed extended rotary handle horizontal 3P 1 direct 7
600 mm Prisma G wall-mounted enclosure FuPact INF100...160 fixed extended rotary handle horizontal 3P 1 direct 7
600 mm Prisma G floor-standing enclosure FuPact INF100...160 fixed extended rotary handle horizontal 4P 1 direct 7
600 mm Prisma G wall-mounted enclosure FuPact INF100...160 fixed extended rotary handle horizontal 4P 1 direct 7
600 mm Prisma G floor-standing enclosure FuPact ISFT100N fixed fuse carriers handle vertical 3P 6 rear connection on busbar 8
600 mm Prisma G wall-mounted enclosure FuPact ISFT100N fixed fuse carriers handle vertical 3P 6 rear connection on busbar 8
600 mm Prisma G floor-standing enclosure FuPact ISFT160 fixed fuse carriers handle horizontal 3P 1 direct 6
600 mm Prisma G wall-mounted enclosure FuPact ISFT160 fixed fuse carriers handle horizontal 3P 1 direct 6
600 mm Prisma G floor-standing enclosure FuPact ISFT160 fixed fuse carriers handle vertical 3P 4 rear connection on busbar 8
600 mm Prisma G wall-mounted enclosure FuPact ISFT160 fixed fuse carriers handle vertical 3P 4 rear connection on busbar 8
300 mm Prisma G floor-standing duct FuPact ISFT160 fixed fuse carriers handle vertical 3P 1 direct 6
300 mm Prisma G wall-mounted duct FuPact ISFT160 fixed fuse carriers handle vertical 3P 1 direct 6
600 mm Prisma G floor-standing enclosure FuPact ISFT250 fixed fuse carriers handle horizontal 3P 1 direct 6
600 mm Prisma G wall-mounted enclosure FuPact ISFT250 fixed fuse carriers handle horizontal 3P 1 direct 6
300 mm Prisma G floor-standing duct FuPact ISFT250 fixed fuse carriers handle vertical 3P 1 direct 9
300 mm Prisma G wall-mounted duct FuPact ISFT250 fixed fuse carriers handle vertical 3P 1 direct 9
600 mm Prisma G floor-standing enclosure EasyPact CVS100...160 without fixed direct front rotary handle horizontal 3P 1 direct with long terminal shield 5
600 mm Prisma G wall-mounted enclosure EasyPact CVS100...160 without fixed direct front rotary handle horizontal 3P 1 direct with long terminal shield 5
600 mm Prisma G floor-standing enclosure EasyPact CVS100...160 without fixed direct front rotary handle horizontal 4P 1 direct with long terminal shield 5
600 mm Prisma G wall-mounted enclosure EasyPact CVS100...160 without fixed direct front rotary handle horizontal 4P 1 direct with long terminal shield 5
600 + 300 mm Prisma G floor-standing enclosure + duct EasyPact CVS100...160 without fixed direct front rotary handle horizontal 3P 1 direct with long terminal shield 4
600 + 300 mm Prisma G wall-mounted enclosure + duct EasyPact CVS100...160 without fixed direct front rotary handle horizontal 3P 1 direct with long terminal shield 4
600 + 300 mm Prisma G floor-standing enclosure + duct EasyPact CVS100...160 without fixed direct front rotary handle horizontal 4P 1 direct with long terminal shield 4
600 + 300 mm Prisma G wall-mounted enclosure + duct EasyPact CVS100...160 without fixed direct front rotary handle horizontal 4P 1 direct with long terminal shield 4
850 mm Prisma G floor-standing enclosure EasyPact CVS100...160 without fixed direct front rotary handle horizontal 3P 1 direct with long terminal shield 4
850 mm Prisma G floor-standing enclosure EasyPact CVS100...160 without fixed direct front rotary handle horizontal 4P 1 direct with long terminal shield 4
600 mm Prisma G floor-standing enclosure EasyPact CVS100...160 without fixed toggle vertical 3P 4 direct with long terminal shield 9
600 mm Prisma G wall-mounted enclosure EasyPact CVS100...160 without fixed toggle vertical 3P 4 direct with long terminal shield 9
600 mm Prisma G floor-standing enclosure EasyPact CVS100...160 without fixed toggle vertical 4P 3 direct with long terminal shield 9
600 mm Prisma G wall-mounted enclosure EasyPact CVS100...160 without fixed toggle vertical 4P 3 direct with long terminal shield 9
600 mm Prisma G floor-standing enclosure EasyPact CVS100...160 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 9
600 mm Prisma G wall-mounted enclosure EasyPact CVS100...160 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 9
600 mm Prisma G floor-standing enclosure EasyPact CVS100...160 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 9
600 mm Prisma G wall-mounted enclosure EasyPact CVS100...160 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 9
300 mm Prisma G floor-standing duct EasyPact CVS100...160 without fixed toggle vertical 3P 1 direct with long terminal shield 9
300 mm Prisma G wall-mounted duct EasyPact CVS100...160 without fixed toggle vertical 3P 1 direct with long terminal shield 9
300 mm Prisma G floor-standing duct EasyPact CVS100...160 without fixed toggle vertical 4P 1 direct with long terminal shield 9
300 mm Prisma G wall-mounted duct EasyPact CVS100...160 without fixed toggle

1 direct with long terminal shield 13
300 mm Prisma G floor-standing duct EasyPact CVS250 with fixed toggle vertical 4P
1 direct with long terminal shield 13
300 mm Prisma G wall-mounted duct EasyPact CVS250 with fixed toggle vertical 4P
1 direct with long terminal shield 13
600 mm Prisma G floor-standing enclosure ComPact NSX100...160 with fixed toggle
vertical 3P 4 direct with long terminal shield 10
600 mm Prisma G wall-mounted enclosure ComPact NSX100...160 with fixed toggle
vertical 3P 4 direct with long terminal shield 10
600 mm Prisma G floor-standing enclosure ComPact NSX100...160 with fixed toggle
vertical 4P 3 direct with long terminal shield 10
600 mm Prisma G wall-mounted enclosure ComPact NSX100...160 with fixed toggle
vertical 4P 3 direct with long terminal shield 10
600 mm Prisma G floor-standing enclosure ComPact NSX100...160 with fixed direct
front rotary handle vertical 3P 4 direct with long terminal shield 10
600 mm Prisma G wall-mounted enclosure ComPact NSX100...160 with fixed direct
front rotary handle vertical 3P 4 direct with long terminal shield 10
600 mm Prisma G floor-standing enclosure ComPact NSX100...160 with fixed direct
front rotary handle vertical 4P 3 direct with long terminal shield 10
600 mm Prisma G wall-mounted enclosure ComPact NSX100...160 with fixed direct
front rotary handle vertical 4P 3 direct with long terminal shield 10
300 mm Prisma G floor-standing duct ComPact NSX100...160 with fixed toggle
vertical 3P 1 direct with long terminal shield 13
300 mm Prisma G wall-mounted duct ComPact NSX100...160 with fixed toggle
vertical 3P 1 direct with long terminal shield 13
300 mm Prisma G floor-standing duct ComPact NSX100...160 with fixed toggle
vertical 4P 1 direct with long terminal shield 13
300 mm Prisma G wall-mounted duct ComPact NSX100...160 with fixed toggle
vertical 4P 1 direct with long terminal shield 13
600 mm Prisma G floor-standing enclosure ComPact NSX250 with fixed toggle
vertical 3P 4 direct with long terminal shield 13
600 mm Prisma G wall-mounted enclosure ComPact NSX250 with fixed toggle
vertical 3P 4 direct with long terminal shield 13
600 mm Prisma G floor-standing enclosure ComPact NSX250 with fixed toggle
vertical 4P 3 direct with long terminal shield 13
600 mm Prisma G wall-mounted enclosure ComPact NSX250 with fixed toggle
vertical 4P 3 direct with long terminal shield 13
600 mm Prisma G floor-standing enclosure ComPact NSX250 with fixed direct front
rotary handle vertical 3P 4 direct with long terminal shield 13
600 mm Prisma G wall-mounted enclosure ComPact NSX250 with fixed direct front
rotary handle vertical 3P 4 direct with long terminal shield 13
600 mm Prisma G floor-standing enclosure ComPact NSX250 with fixed direct front
rotary handle vertical 4P 3 direct with long terminal shield 13
600 mm Prisma G wall-mounted enclosure ComPact NSX250 with fixed direct front
rotary handle vertical 4P 3 direct with long terminal shield 13
300 mm Prisma G floor-standing duct ComPact NSX250 with fixed toggle vertical 3P
1 direct with long terminal shield 13
300 mm Prisma G wall-mounted duct ComPact NSX250 with fixed toggle vertical 3P
1 direct with long terminal shield 13
300 mm Prisma G floor-standing duct ComPact NSX250 with fixed toggle vertical 4P
1 direct with long terminal shield 13
300 mm Prisma G wall-mounted duct ComPact NSX250 with fixed toggle vertical 4P
1 direct with long terminal shield 13

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.6 cm
Package 1 Width	11.3 cm
Package 1 Length	18.5 cm
Package 1 Weight	430 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Packaging

EU RoHS Directive	Compliant
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes

Use Longer

Lifetime extension

Repair	No
--------	----

Use Again

Repack and remanufacture

Take-back	No
-----------	----