

# Product datasheet

Specifications



## TeSys Deca contactor - 3P(3 NO) - AC-3 - <= 440 V 25 A - 380 V AC coil

LC1D253Q7

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

### Main

|                                |                                                                                                                  |
|--------------------------------|------------------------------------------------------------------------------------------------------------------|
| Range                          | TeSys                                                                                                            |
| Range of product               | TeSys Deca                                                                                                       |
| Product or component type      | Contactors                                                                                                       |
| Device short name              | LC1D                                                                                                             |
| Contactors application         | Motor control<br>Resistive load                                                                                  |
| Utilisation category           | AC-4<br>AC-3<br>AC-1                                                                                             |
| Poles description              | 3P                                                                                                               |
| [Ue] rated operational voltage | Power circuit: <= 690 V AC 25...400 Hz<br>Power circuit: <= 300 V DC                                             |
| [Ie] rated operational current | 25 A (at <60 °C) at <= 440 V AC AC-3 for power circuit<br>40 A (at <60 °C) at <= 440 V AC AC-1 for power circuit |
| [Uc] control circuit voltage   | 380 V AC 50/60 Hz                                                                                                |

### Complementary

|                                             |                                                                                                                                                                                                                                                                                                                            |
|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Motor power kW                              | 5.5 kW at 220...230 V AC 50/60 Hz (AC-3)<br>11 kW at 380...400 V AC 50/60 Hz (AC-3)<br>11 kW at 415...440 V AC 50/60 Hz (AC-3)<br>15 kW at 500 V AC 50/60 Hz (AC-3)<br>15 kW at 660...690 V AC 50/60 Hz (AC-3)<br>5.5 kW at 400 V AC 50/60 Hz (AC-4)                                                                       |
| Motor power hp                              | 3 hp at 230/240 V AC 50/60 Hz for 1 phase motors<br>2 hp at 115 V AC 50/60 Hz for 1 phase motors<br>7.5 hp at 230/240 V AC 50/60 Hz for 3 phases motors<br>15 hp at 460/480 V AC 50/60 Hz for 3 phases motors<br>20 hp at 575/600 V AC 50/60 Hz for 3 phases motors<br>7.5 hp at 200/208 V AC 50/60 Hz for 3 phases motors |
| Compatibility code                          | LC1D                                                                                                                                                                                                                                                                                                                       |
| Pole contact composition                    | 3 NO                                                                                                                                                                                                                                                                                                                       |
| Protective cover                            | With                                                                                                                                                                                                                                                                                                                       |
| [Ith] conventional free air thermal current | 25 A (at 60 °C) for power circuit<br>10 A (at 60 °C) for signalling circuit                                                                                                                                                                                                                                                |
| Irms rated making capacity                  | 140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A DC for signalling circuit conforming to IEC 60947-5-1<br>450 A at 440 V for power circuit conforming to IEC 60947                                                                                                                                     |
| Rated breaking capacity                     | 450 A at 440 V for power circuit conforming to IEC 60947                                                                                                                                                                                                                                                                   |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                                 |                                                                                                                                                                                                                                                                                                                                                                          |
|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>[Icw] rated short-time withstand current</b> | 240 A 40 °C - 10 s for power circuit<br>380 A 40 °C - 1 s for power circuit<br>50 A 40 °C - 10 min for power circuit<br>120 A 40 °C - 1 min for power circuit<br>100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit                                                                                    |
| <b>Associated fuse rating</b>                   | 10 A gG for signalling circuit conforming to IEC 60947-5-1<br>63 A gG at <= 690 V coordination type 1 for power circuit<br>40 A gG at <= 690 V coordination type 2 for power circuit                                                                                                                                                                                     |
| <b>Average impedance</b>                        | 2 mOhm - lth 25 A 50 Hz for power circuit                                                                                                                                                                                                                                                                                                                                |
| <b>Power dissipation per pole</b>               | 3.2 W AC-1<br>1.25 W AC-3                                                                                                                                                                                                                                                                                                                                                |
| <b>[Ui] rated insulation voltage</b>            | Power circuit: 690 V conforming to IEC 60947-4-1<br>Power circuit: 600 V CSA certified<br>Power circuit: 600 V UL certified<br>Signalling circuit: 690 V conforming to IEC 60947-1<br>Signalling circuit: 600 V CSA certified<br>Signalling circuit: 600 V UL certified                                                                                                  |
| <b>Overvoltage category</b>                     | III                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Pollution degree</b>                         | 3                                                                                                                                                                                                                                                                                                                                                                        |
| <b>[Uimp] rated impulse withstand voltage</b>   | 6 kV conforming to IEC 60947                                                                                                                                                                                                                                                                                                                                             |
| <b>Safety reliability level</b>                 | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1                                                                                                                                                                                                     |
| <b>Mechanical durability</b>                    | 15 Mcycles                                                                                                                                                                                                                                                                                                                                                               |
| <b>Electrical durability</b>                    | 1.65 Mcycles 25 A AC-3 at Ue <= 440 V<br>1.4 Mcycles 40 A AC-1 at Ue <= 440 V                                                                                                                                                                                                                                                                                            |
| <b>Control circuit type</b>                     | AC at 50/60 Hz                                                                                                                                                                                                                                                                                                                                                           |
| <b>Coil technology</b>                          | Without built-in suppressor module                                                                                                                                                                                                                                                                                                                                       |
| <b>Control circuit voltage limits</b>           | 0.3...0.6 Uc (-40...70 °C):drop-out AC 50/60 Hz<br>0.8...1.1 Uc (-40...60 °C):operational AC 50 Hz<br>0.85...1.1 Uc (-40...60 °C):operational AC 60 Hz<br>1...1.1 Uc (60...70 °C):operational AC 50/60 Hz                                                                                                                                                                |
| <b>Inrush power in VA</b>                       | 70 VA 60 Hz cos phi 0.75 (at 20 °C)<br>70 VA 50 Hz cos phi 0.75 (at 20 °C)                                                                                                                                                                                                                                                                                               |
| <b>Hold-in power consumption in VA</b>          | 7.5 VA 60 Hz cos phi 0.3 (at 20 °C)<br>7 VA 50 Hz cos phi 0.3 (at 20 °C)                                                                                                                                                                                                                                                                                                 |
| <b>Heat dissipation</b>                         | 2...3 W at 50/60 Hz                                                                                                                                                                                                                                                                                                                                                      |
| <b>Operating time</b>                           | 12...22 ms closing<br>4...19 ms opening                                                                                                                                                                                                                                                                                                                                  |
| <b>Connections - terminals</b>                  | Control circuit: spring terminals 1 2.5 mm² - cable stiffness: flexible without cable end<br>Control circuit: spring terminals 2 2.5 mm² - cable stiffness: flexible without cable end<br>Power circuit: spring terminals 1 4 mm² - cable stiffness: flexible without cable end<br>Power circuit: spring terminals 2 4 mm² - cable stiffness: flexible without cable end |
| <b>Auxiliary contact composition</b>            | 1 NO + 1 NC                                                                                                                                                                                                                                                                                                                                                              |
| <b>Auxiliary contacts type</b>                  | type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1                                                                                                                                                                                                                                                 |
| <b>Signalling circuit frequency</b>             | 25...400 Hz                                                                                                                                                                                                                                                                                                                                                              |
| <b>Minimum switching voltage</b>                | 17 V for signalling circuit                                                                                                                                                                                                                                                                                                                                              |
| <b>Minimum switching current</b>                | 5 mA for signalling circuit                                                                                                                                                                                                                                                                                                                                              |
| <b>Insulation resistance</b>                    | > 10 MOhm for signalling circuit                                                                                                                                                                                                                                                                                                                                         |
| <b>Non-overlap time</b>                         | 1.5 ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact                                                                                                                                                                                                                                                                  |

|                  |       |
|------------------|-------|
| Mounting support | Plate |
|                  | Rail  |

## Environment

|                                                       |                                                                                                                                                                                       |
|-------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards                                             | CSA C22.2 No 14<br>EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508                                                                                           |
| Product certifications                                | DNV<br>CCC<br>GOST<br>RINA<br>GL<br>UL<br>LROS (Lloyds register of shipping)<br>CSA<br>BV                                                                                             |
| IP degree of protection                               | IP20 front face conforming to IEC 60529                                                                                                                                               |
| Protective treatment                                  | TH conforming to IEC 60068-2-30                                                                                                                                                       |
| Climatic withstand                                    | conforming to IACS E10 exposure to damp heat<br>conforming to IEC 60947-1 Annex Q category D exposure to damp heat                                                                    |
| Permissible ambient air temperature around the device | -40...60 °C<br>60...70 °C with derating                                                                                                                                               |
| Operating altitude                                    | 0...3000 m                                                                                                                                                                            |
| Fire resistance                                       | 850 °C conforming to IEC 60695-2-1                                                                                                                                                    |
| Flame retardance                                      | V1 conforming to UL 94                                                                                                                                                                |
| Mechanical robustness                                 | Vibrations contactor open (2 Gn, 5...300 Hz)<br>Vibrations contactor closed (4 Gn, 5...300 Hz)<br>Shocks contactor closed (15 Gn for 11 ms)<br>Shocks contactor open (8 Gn for 11 ms) |
| Height                                                | 99 mm                                                                                                                                                                                 |
| Width                                                 | 45 mm                                                                                                                                                                                 |
| Depth                                                 | 92 mm                                                                                                                                                                                 |
| Net weight                                            | 0.37 kg                                                                                                                                                                               |

## Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type of Package 1       | PCE |
| Number of Units in Package 1 | 1   |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

| Materials and Substances |                           |
|--------------------------|---------------------------|
| EU RoHS Directive        | <a href="#">Compliant</a> |
| PVC free                 | Yes                       |

### Use Longer

| Lifetime extension |    |
|--------------------|----|
| Repair             | No |

### Use Again

| Repack and remanufacture        |                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| End of life manual availability | <a href="#">End of Life Information</a>                                                                                                                                                                         |
| WEEE Label                      |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |