

Product datasheet

Specifications



auxiliary contact - 4 NO/NC standard - navy - Masterpact NW

64556

Main

Product or component type	Auxiliary contact
Device short name	4 OF
Range compatibility	Masterpact MasterPact NW
Signal contacts composition	4 NO/NC

Complementary

Auxiliary contacts type	Standard
Breaking capacity (A)	AC-12: 10 A at 240/380 V AC 50/60 Hz AC-12: 10 A at 480 V AC 50/60 Hz AC-12: 6 A at 690 V AC 50/60 Hz DC-12: 10 A at 125 V DC DC-12: 3 A at 250 V DC DC-12: 10 A at 24/48 V DC
Minimum load	100 mA at 24 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	4.5 cm
Package 1 Length	4.5 cm
Package 1 Weight	100.0 g

Contractual warranty

Warranty (in months)	18
----------------------	----

Excluding VAT, FCA Jabal Ali & amp; are subject to change – check with your local distributor.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins