


Product datasheet

Specifications



Servo motor BEH18, Lexium 18, 1.3kW, 220V, M130, 17bit, MAG MT, brake

BEH18MM1313MF6C

Main

Range	Lexium 18
Range compatibility	Easy Lexium 18
Device short name	BEH18
Product or component type	Servo motor

Complementary

Maximum mechanical speed	3000.0 rpm
[Us] rated supply voltage	220 V
Network number of phases	Single phase
Continuous stall current	9.4 A
Continuous stall torque	8.34 N.m, 220 V, single phase
Continuous power	1300 W
Peak stall torque	25.02 N.m, 220 V, single phase
Nominal output power	1300 W, 220 V, single phase
Nominal torque	8.34 N.m, 220 V, single phase
Nominal speed	1500 rpm, 220 V, single phase
Maximum current Irms	at 1.3 kW, 220 V
Maximum permanent current	27 A
Product compatibility	Motion servo drive motion servo motors motor at 1.3 kW, 220 V, single phase
Shaft end	Parallel key
Shaft diameter	22.0 mm
Shaft length	58.0 mm
Feedback type	17 bits magnetic multi turn encoder
Speed feedback resolution	131072 points/turn
Holding brake	With
Holding torque	16 N.m
Mounting support	Asian standard flange
Motor flange size	130 mm
Electrical connection	2 connectors male/female
Torque constant	0.887 N.m/A at 40 °C
Back emf constant	63.21 V/krpm at 40 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of motor poles	10
Rotor inertia	21.85 kg.cm ²
Maximum radial force Fr	686 N
Maximum axial force Fa	196 N
Length	183.6 mm
Number of mounting holes	4
Circle diameter of the mounting holes	9 mm
Width	183.6 mm
Height	130 mm
Depth	174.5 mm
Product weight	9.1 kg
Network number of phases	3
Encoder type	Magnetic encoder

Environment

IP degree of protection	IP67
Ambient air temperature for operation	0...40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20 cm
Package 1 Width	29.9 cm
Package 1 Length	39.8 cm
Package 1 Weight	10.9 kg
Unit Type of Package 2	P06
Number of Units in Package 2	16
Package 2 Height	95 cm
Package 2 Width	60 cm
Package 2 Length	80 cm
Package 2 Weight	180.4 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	9 271 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	67 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	9 184 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	17 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

End of life manual availability	End of Life Information
Take-back	No

Image of product / Alternate images

Alternative



