



### Catalog No. TLM2012CCURP

Description: 125A 20 CIRC INDOOR RISER PANEL

UPC No 783164287899

Home > Load Centers > Load Centers

PowerMark Gold convertible riser panels arrive as main lug, but have the capability to have a main breaker installed. All ABB load centers are rated up to 60 degree/75 degree centigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TLM2012CCURP features space for 20, 1" breakers, a 125 A bus ampere rating, a copper bus, and a combination/flush enclosure. Tap kits are required and can be ordered separately.



Representative Image

#### Descriptors

Category	Load Centers
GO Schedule	RA
Grouping	Single Phase - USA

#### Specifications

Load Center Type	Riser
Input/Output Voltage	120/240V ac
Interrupting Capacity Rating	22
Amperage	125 A
Device type	Main Lug
Enclosure	Indoor
Phase	1 Phase
1" Space	20
1/2" Space	40
Feed	Either
Door	Yes
GSA Compliance	No
Circuit Breaker Style	Plug-In
NEMA Rating	NEMA 1
Factory Installed Ground Kit	No
Enclosure Type	Indoor, Combination
Wires	3 Wire
Service & Voltage	1 Phase, 3 Wire, 120/240V ac

#### Classifications

UL/CUL Listing	UL
----------------	----





## Publications

Title	Publication No.	Publication Type
<a href="#">Section 1 BuyLog: Load centers and circuit breakers</a> Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line.	DET1023	Application and Technical

**Additional Documentation:** Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.