

Product data sheet

Specifications



TeSys F - suppressor module - bidirectional diode - 50...110 V AC/DC

LA4FTF

⚠ Discontinued on: Jul 2, 2025

⚠ Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	TeSys
Device short name	LA4F
Product or Component Type	Suppressor module
Product Compatibility	LC1F

Complementary

Mounting Mode	By clips
Suppressor technology	Bidirectional peak limiting diode
[Uc] control circuit voltage	50...110 V AC 50...110 V DC
Maximum peak voltage	2...2.5 Uc
Net Weight	0.09 lb(US) (0.04 kg)

Environment

Product Certifications	UKCA
------------------------	------

Ordering and shipping details

Category	US10I1222341
Discount Schedule	0I12
GTIN	3389110273663
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.6 in (4.0 cm)
Package 1 Width	2.0 in (5.0 cm)
Package 1 Length	2.0 in (5.0 cm)
Package weight(Lbs)	1.7 oz (48.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	70

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Height	5.9 in (15.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	7.699 lb(US) (3.492 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint of the manufacturing phase [A1 to A3]	0.4 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.

Use Better



Materials and Substances

EU RoHS Directive	Compliant with Exemptions
-----------------------------------	---------------------------

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	20
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.