

Product datasheet

Specifications



Multi-function overload relay, EOCR Digital, 0.5 to 60A, 85 to 250VAC/ DC

EOCRPFZ-WRDUH

Main

Range of product	EOCR
Device short name	EOCR-PFZ
Product or component type	Multifunction protection relay
Protection type	Overload, In > OC setting Underload, In < UC setting Locked rotor for running, In > 1.5...5 times OC setting Sensitivity to phase loss Earth fault, Ig > Ig setting Sensitivity to phase reverse Locked rotor for starting, In > 2...10 times OC setting Phase unbalance, 5...50 %
Product specific application	Overload protection
Analogue output range	4...20 mA
Network type	AC
Network frequency	50...60 Hz
protection ajustment range	0.5...60 A
Tripping threshold	0.03...10 A, off (definite) - earth fault current 0.5...60 A 0.03...1 A (inverse) - earth fault current

Complementary

[Us] rated supply voltage	85...250 V AC/DC
Mounting support	Base unit: 35 mm DIN rail Base unit: panel Display unit: flush
Contacts type and composition	1 NC + 1 NO (OL) 1 NO (GR)
Short-circuit and overload protection	By 4 A gG fuse
[Ue] rated operational voltage	600 V AC 50...60 Hz for power circuit conforming to UL 690 V AC 50...60 Hz for power circuit conforming to CSA 690 V AC 50...60 Hz for power circuit conforming to IEC 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-4-1
Reset	Manual reset Electrical 0...1 s by interruption of power supply Automatic reset 0.3...1200 s
Time delay type	O-Time: 0.2...30 s (definite) D-Time: 1...200 s, off U-Time: 0.5...30 s Ed-Time: 1...10 s, off O-Time: 1...30 class (inverse) E-Time: 0.05, 0.1...10 s (definite) E-Time: 0.05...10 class (inverse)

Excluding VAT, FCA Jabal Ali & amp; are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Display type	Bar graph 7 segments LED
power consumption per relay	3 W
Connections - terminals	Control circuit: cable 2 x 1...1.5 mm²flexible with cable end - M3 Control circuit: cable 2 x 1...1.5 mm²flexible without cable end - M3 Control circuit: cable 1 x 1...2.5 mm²flexible with cable end - M3 Control circuit: cable 1 x 1...2.5 mm²flexible without cable end - M3
Tightening torque	Control circuit: 0.8...1.2 N.m on cable, 4.7 mm
Height	50 mm
Width	90 mm
Depth	110 mm
Product weight	0.679 kg

Environment

Standards	IEC 60947-4-1
IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-20...60 °C conforming to IEC 60947-4-1
Ambient air temperature for storage	-30...80 °C
Operating altitude	2000 m
Fire resistance	650 °C conforming to IEC 60695-2-12 960 °C conforming to UL 94
Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-7
Vibration resistance	4 gn on panel mounting conforming to IEC 60068-2-6 2 gn on 35 mm DIN rail conforming to IEC 60068-2-6
Dielectric strength	2 kV 50...60 Hz in between case and circuit conforming to IEC 60255-5 1 kV 50...60 Hz in between contact conforming to IEC 60255-5 2 kV 50...60 Hz in between circuit conforming to IEC 60255-5
Surge withstand	6 kV conforming to IEC 61000-4-5
Electromagnetic compatibility	Resistance to radiated electromagnetic fields: 10 V/m level 3 conforming to IEC 61000-4-3 Resistance to electrostatic discharge: 8 kV air, 6 kV contact conforming to IEC 61000-4-2 Resistance to fast transient: 2 kV conforming to IEC 61000-4-4 Conducted RF disturbances: 10 V conforming to EN 61000-4-6 Conducted RF disturbances: class A conforming to EN 55011
[Ith] conventional free air thermal current	5 A for control circuit
Permissible current	250 V, 5 A

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.001 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	440635ef-4ab9-4af3-beec-63d4c8a6a97d
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No