



circuit breaker 3VA1 IEC Frame 160 breaking capacity class S  $I_{cu}=36 \text{ kA} @ 415 \text{ V}$   
 3-pole, line protection TM210, FTFM,  $I_n=40 \text{ A}$  overload protection  $I_r=40 \text{ A}$   
 permanently set short-circuit protection  $I_i=10 \times I_n$  terminal connection

| Model   |                             |
|---|-----------------------------|
| product brand name  | SENTRON                     |
| product designation   | Molded case circuit breaker |
| design of the product   | Line protection             |
| design of the overcurrent release   | TM210                       |
| protection function of the overcurrent release  | LI                          |
| number of poles   | 3                           |
| General technical data  |                             |
| insulation voltage / rated value  | 800 V                       |
| operating voltage / at DC / rated value   | 500 V                       |
| operating voltage / at AC / rated value   | 690 V                       |
| power loss [W] / maximum  | 10.8 W                      |
| mechanical service life (operating cycles) / typical  | 20 000                      |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V                                      | 9 000                       |
| electrical endurance (operating cycles) / at AC-1 / at 690 V  | 6 300                       |
| product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof | No                          |
| ground-fault monitoring version   | Without                     |
| product function  |                             |
| • communication function  | No                          |
| • other measurement function  | No                          |
| Net Weight  | 977 g                       |
| Current   |                             |
| operational current   |                             |
| • at 40 °C  | 40 A                        |
| • at 45 °C  | 40 A                        |
| • at 50 °C  | 40 A                        |
| • at 55 °C  | 39 A                        |
| • at 60 °C  | 39 A                        |
| • at 65 °C  | 38 A                        |
| • at 70 °C  | 37 A                        |
| Switching capacity according to IEC 60947   |                             |
| switching capacity class of the circuit breaker   | S                           |
| maximum short-circuit current breaking capacity ( $I_{cu}$ )  |                             |
| • at 240 V  | 55 kA                       |
| • at 415 V  | 36 kA                       |
| • at 440 V  | 25 kA                       |
| • at 500 V  | 7 kA                        |
| • at 690 V  | 7 kA                        |

|  |  |
|--|--|
| operating short-circuit current breaking capacity (Ics)  |  |
| <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 440 V</li> <li>• at 500 V</li> <li>• at 690 V</li> </ul> | <ul style="list-style-type: none"> <li>55 kA</li> <li>36 kA</li> <li>25 kA</li> <li>5 kA</li> <li>5 kA</li> </ul>  |
| short-circuit current making capacity (Icm)  |  |
| <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 440 V</li> <li>• at 500 V</li> <li>• at 690 V</li> </ul> | <ul style="list-style-type: none"> <li>121 kA</li> <li>75.5 kA</li> <li>52.5 kA</li> <li>11.9 kA</li> <li>11.9 kA</li> </ul>                                   |
| design of short-circuit protection   | For switching power values in DC networks, see the 3VA molded case circuit breaker device manual; link to be found under Service & Support in the last chapter |

#### Adjustable parameters

|   |  |
|---|--|
| product feature / for L-tripping / can be switched on/off   | No   |
| adjustable response value setting current (I <sub>r</sub> ) / of the L-trip / with I <sub>2t</sub> characteristic |  |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                                    | <ul style="list-style-type: none"> <li>40 A</li> <li>40 A</li> </ul>   |
| adjustable response value delay time (t <sub>r</sub> ) / for L-tripping / with I <sub>2t</sub> characteristic     |  |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                                    | <ul style="list-style-type: none"> <li>1 s</li> <li>1 s</li> </ul>     |
| adjustable response value setting current (I <sub>i</sub> ) / for I-tripping                                      |  |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                                    | <ul style="list-style-type: none"> <li>400 A</li> <li>400 A</li> </ul> |
| adjustable setting current (I <sub>nN</sub> ) / for N-tripping  |  |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                                    | <ul style="list-style-type: none"> <li>0 A</li> <li>0 A</li> </ul>     |
| product function / grounding protection   | No   |

#### Mechanical Design

|   |  |
|---|--|
| product component   |  |
| <ul style="list-style-type: none"> <li>• undervoltage release</li> <li>• voltage trigger</li> <li>• trip indicator</li> </ul> | <ul style="list-style-type: none"> <li>No</li> <li>No</li> <li>No</li> </ul> |
| height [in]   | 5.12 in  |
| height  | 130 mm   |
| width [in]  | 3 in   |
| type of connectable conductor cross-sections / of the round conductor terminal / stranded                                     | 1 x (1,5 - 70 mm <sup>2</sup> )  |
| width   | 76.2 mm  |
| depth [in]  | 2.76 in  |
| depth   | 70 mm  |

#### Connections

|   |                            |
|---|----------------------------|
| arrangement of electrical connectors / for main current circuit                       | Front terminal             |
| type of electrical connection / for main current circuit                              | box terminal on both sides |
| design of the surface / of the connections / on the top of the switch (N, 1, 3, 5)    | Silver                     |
| design of the surface / of the connections / on the bottom of the switch (N, 2, 4, 6) | Tin                        |

#### Auxiliary circuit

|  |   |
|--|---|
| number of CO contacts / for auxiliary contacts | 0 |
|--|---|

#### Accessories

|  |     |
|--|-----|
| product extension / optional / motor drive | Yes |
|--|-----|

#### Environmental conditions

|  |   |
|--|---|
| protection class IP / on the front   | IP40  |
| ambient temperature  |   |
| <ul style="list-style-type: none"> <li>• during operation / minimum</li> <li>• during operation / maximum</li> </ul> | <ul style="list-style-type: none"> <li>-25 °C</li> <li>70 °C</li> </ul> |

- during storage / minimum -40 °C
- during storage / maximum 80 °C

### Environmental footprint

|  |           |
|--|-----------|
| Environmental Product Declaration(EPD)                   | Yes       |
| global warming potential [CO2 eq] / total                | 190 kg    |
| global warming potential [CO2 eq] / during manufacturing | 4.67 kg   |
| global warming potential [CO2 eq] / during operation     | 186 kg    |
| global warming potential [CO2 eq] / after end of life    | -0.826 kg |
| reference code / according to IEC 81346-2                | Q         |

### Approvals / Certificates

#### General Product Approval



[Miscellaneous](#)



#### General Product Approval

#### EMV

#### Test Certificates

[Confirmation](#)



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

#### Test Certificates

#### Maritime application

[Miscellaneous](#)



#### Maritime application

#### other

#### Environment

[CCS \(China Classification Society\)](#)

[Miscellaneous](#)

[Confirmation](#)



[Environmental Confirmations](#)



#### Environment



[Environmental Confirmations](#)

### Further information

#### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

#### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA1140-4ED36-0AA0>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA1140-4ED36-0AA0>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA1140-4ED36-0AA0](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA1140-4ED36-0AA0)

#### CAX-Online-Generator

<https://www.siemens.com/cax>

#### Tender specifications

<https://www.siemens.com/specifications>

#### Characteristic curves





