

MPZB25S40F

Mini Power Zone unit substation, bolt on branch, 1 phase, 25kVA, 480V primary, 120/240V secondary, Type 3R

Main

Product	Sealed Transformer
Certifications	UL Listed
Type	Mini Power-Zone
Enclosure Code	BB
Insulation Temperature	365 °F (185 °C)
Phase	1 phase
Primary Voltage	480 V
Secondary Voltage	120/240 V
Full Capacity Taps	2 5 % FCBN
Power Rating	25 kVA
Temperature Rise	115 °C
Winding Material	Copper
Interrupt Rating	18 kA
Circuit Breaker Type	Primary main breaker Secondary main breaker Feeder breaker
Interior Type	NQ Panelboard interior
Number of Spaces Available	28
Number of Circuits	28
Enclosure Type	NEMA 3R hot-rolled steel

Ordering and shipping details

Category	16276-MPZ BOLT-ON BRANCH CB
Discount Schedule	PE2
GTIN	785901084358
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.49 in (36.8 cm)
Package 1 Width	23.11 in (58.7 cm)
Package 1 Length	52.64 in (133.7 cm)
Package 1 Weight	490.00 lb(US) (222.26 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration

RoHS exemption information	 Yes
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------