

# Product datasheet

Specifications



## Circuit breaker, ComPact NSX400F, 36kA/415VAC, MicroLogic 7.3E Vigi trip unit 400A, 3 poles 3d

LV434631

 **Discontinued on:** 30 Jun 2023

 **Discontinued**

### Main

|                                                      |                                                                                                                                                                                          |
|------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                                | ComPact                                                                                                                                                                                  |
| Product name                                         | ComPact NSX                                                                                                                                                                              |
| Range of product                                     | ComPact NSX400...630                                                                                                                                                                     |
| Device short name                                    | NSX400F                                                                                                                                                                                  |
| Product or component type                            | Earth leakage circuit breaker                                                                                                                                                            |
| Device application                                   | Distribution                                                                                                                                                                             |
| Number of poles                                      | 3P                                                                                                                                                                                       |
| Protected poles description                          | 3t                                                                                                                                                                                       |
| [In] rated current                                   | 400 A at 40 °C                                                                                                                                                                           |
| [Ue] rated operational voltage                       | 440 V AC 50/60 Hz                                                                                                                                                                        |
| Network type                                         | AC                                                                                                                                                                                       |
| Network frequency                                    | 50/60 Hz                                                                                                                                                                                 |
| Suitability for isolation                            | Yes conforming to EN/IEC 60947-2                                                                                                                                                         |
| Utilisation category                                 | Category A                                                                                                                                                                               |
| [Icu] rated ultimate short-circuit breaking capacity | 40 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>36 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>30 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level                                    | F 36 kA 415 V AC                                                                                                                                                                         |
| Trip unit name                                       | MicroLogic 7.3 E                                                                                                                                                                         |
| Trip unit technology                                 | Electronic                                                                                                                                                                               |
| Trip unit protection functions                       | LSIR                                                                                                                                                                                     |
| Control type                                         | Toggle                                                                                                                                                                                   |
| Circuit breaker mounting mode                        | Fixed                                                                                                                                                                                    |

### Complementary

|                                                     |                                                                                                                                                                              |
|-----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ui] rated insulation voltage                       | 500 V AC 50/60 Hz                                                                                                                                                            |
| [Uimp] rated impulse withstand voltage              | 8 kV                                                                                                                                                                         |
| [Ics] rated service short-circuit breaking capacity | 40 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>36 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>30 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability                               | 20000 cycles                                                                                                                                                                 |
| Electrical durability                               | 6000 cycles at 440 V In<br>12000 cycles at 440 V In/2                                                                                                                        |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                                             |                                                                                                                                                                              |
|-------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mounting support                                            | Backplate                                                                                                                                                                    |
| Upside connection                                           | Front                                                                                                                                                                        |
| Downside connection                                         | Front                                                                                                                                                                        |
| Connection pitch                                            | 45 mm                                                                                                                                                                        |
| Protection type                                             | L : for overload protection (long time)<br>S : for short time short-circuit protection<br>I : for instantaneous short-circuit protection<br>R : for earth-leakage protection |
| Trip unit rating                                            | 400 A at 40 °C                                                                                                                                                               |
| Long-time pick-up adjustment type Ir (thermal protection)   | Adjustable 9 settings                                                                                                                                                        |
| [Ir] long-time protection pick-up adjustment range          | 160...400 A                                                                                                                                                                  |
| Long-time protection delay adjustment type tr               | Adjustable                                                                                                                                                                   |
| [tr] long-time protection delay adjustment range            | 15...400 s at 1.5 x Ir<br>0.5...16 s at 6 x Ir<br>0.35...11 s at 7.2 x Ir                                                                                                    |
| Thermal memory                                              | 20 minutes before and after tripping                                                                                                                                         |
| Short-time protection pick-up adjustment type Isd           | Adjustable                                                                                                                                                                   |
| [Isd] Short-time protection pick-up adjustment range        | 1.5...10 x Ir                                                                                                                                                                |
| Short-time protection delay adjustment type tsd             | Adjustable                                                                                                                                                                   |
| [tsd] Short-time protection delay adjustment range          | 0...0.4 s                                                                                                                                                                    |
| Instantaneous protection pick-up adjustment type Ii         | Adjustable                                                                                                                                                                   |
| [Ii] instantaneous protection pick-up adjustment range      | 1.5...12 x In                                                                                                                                                                |
| Earth-leakage protection                                    | Integrated                                                                                                                                                                   |
| Earth-leakage protection class                              | Class A                                                                                                                                                                      |
| Earth-leakage protection sensitivity adjustment type IΔn    | Adjustable                                                                                                                                                                   |
| [IΔn] earth-leakage protection sensitivity adjustment range | 300 mA<br>500 mA<br>1 A<br>3 A<br>5 A<br>10 A                                                                                                                                |
| Earth-leakage protection specific mode                      | OFF using the IΔn rotary switch                                                                                                                                              |
| Earth-leakage protection time delay adjustment type Δt      | Adjustable                                                                                                                                                                   |
| [Δt] Earth-leakage protection time delay adjustment range   | 0 ms<br>60 ms<br>150 ms<br>500 ms<br>1 s                                                                                                                                     |
| Zone selective interlocking ZSI                             | Without                                                                                                                                                                      |
| Number of slots for electrical auxiliaries                  | 6 slot(s)                                                                                                                                                                    |
| Local signalling                                            | Flashing LED (green) for ready to operate<br>LED 105 % Ir (red) for overload<br>LED 90 % Ir (orange) for overload                                                            |
| Display type                                                | LCD display                                                                                                                                                                  |
| Type of measurement                                         | Energy meter                                                                                                                                                                 |
| Width (W)                                                   | 140 mm                                                                                                                                                                       |

|            |         |
|------------|---------|
| Height (H) | 255 mm  |
| Depth (D)  | 110 mm  |
| Net weight | 6.05 kg |

## Environment

|                                       |                                                              |
|---------------------------------------|--------------------------------------------------------------|
| Standards                             | EN/IEC 60947                                                 |
| Product certifications                | CCC<br>EAC<br>Marine                                         |
| Overvoltage category                  | Class II                                                     |
| Electrical shock protection class     | Class II                                                     |
| Pollution degree                      | 3 conforming to IEC 60664-1                                  |
| IP degree of protection               | IP40 conforming to IEC 60529                                 |
| IK degree of protection               | IK07 conforming to IEC 62262                                 |
| Ambient air temperature for operation | -25...70 °C                                                  |
| Ambient air temperature for storage   | -40...85 °C                                                  |
| Relative humidity                     | 0...95 %                                                     |
| Operating altitude                    | 0...2000 m without derating<br>2000 m...5000 m with derating |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 16.8 cm |
| Package 1 Width              | 25.5 cm |
| Package 1 Length             | 14.0 cm |
| Package 1 Weight             | 7.5 kg  |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

| Materials and Substances |                           |
|--------------------------|---------------------------|
| EU RoHS Directive        | <a href="#">Compliant</a> |

### Use Longer

| Lifetime extension |    |
|--------------------|----|
| Repair             | No |

### Use Again

| Repack and remanufacture |                                                                                                                                                                                                                 |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WEEE Label               |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |