

# Product datasheet

Specifications



## TeSys F - suppressor module - bidirectional diode - 127...240 V AC/ DC

LA4FTP

### Main

|                           |                   |
|---------------------------|-------------------|
| Range                     | TeSys             |
| Device short name         | LA4F              |
| Product or component type | Suppressor module |
| Product compatibility     | LC1F              |

### Complementary

|                              |                                   |
|------------------------------|-----------------------------------|
| Mounting mode                | By clips                          |
| Suppressor technology        | Bidirectional peak limiting diode |
| [Uc] control circuit voltage | 127...240 V AC<br>127...240 V DC  |
| Maximum peak voltage         | 2...2.5 Uc                        |
| Net weight                   | 0.04 kg                           |

### Environment

|                        |      |
|------------------------|------|
| Product certifications | UKCA |
|------------------------|------|

### Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 4.0 cm   |
| Package 1 Width              | 5.0 cm   |
| Package 1 Length             | 5.0 cm   |
| Package 1 Weight             | 37.0 g   |
| Unit Type of Package 2       | S02      |
| Number of Units in Package 2 | 70       |
| Package 2 Height             | 15.0 cm  |
| Package 2 Width              | 30.0 cm  |
| Package 2 Length             | 40.0 cm  |
| Package 2 Weight             | 3.085 kg |

### Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

[EU RoHS Directive](#)

Compliant with Exemptions

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

End of life manual availability

No need of specific recycling operations

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins