

Product datasheet

Specifications



Vigi iC60 - earth leakage add-on block - 1P + N - 25A - 10mA - A type

A9V00625

EAN Code: 3606480551789

! Discontinued

Main

| | |
|-------------------------------------|---|
| Range | Acti9 |
| Product name | Acti9 Vigi iC60 |
| Product or component type | Add-on residual current device |
| Device short name | Vigi iC60 |
| Poles description | 1P + N |
| Neutral position | Left |
| [In] rated current | 25 A |
| Earth-leakage sensitivity | 10 mA |
| Earth-leakage protection time delay | Instantaneous |
| Earth leakage protection type | Type A |
| Network type | AC |
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | 240 V AC 50/60 Hz conforming to IEC 61009-1 |
| Standards | IEC 61009-1 EN 61009-1 |
| 9 mm pitches | 4 |

Complementary

| | |
|--|---|
| Device location in system | Outgoer |
| Residual current tripping technology | Voltage independent |
| [Ui] rated insulation voltage | 500 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947-2 |
| Range compatibility | Acti 9 Acti9 iC60 |
| Product compatibility | Single terminal |
| Local signalling | Trip indicator |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| Electrical connection to mcb | By screws |
| Comb busbar and distribution block compatibility | Bottom: YES |
| Height | 91 mm |

| | |
|--------------------------------|--|
| Width | 54 mm |
| Depth | 73.5 mm |
| Net weight | 0.165 kg |
| Connections - terminals | Tunnel type terminal downside for 1 cable(s) 1...25 mm ² rigid without cable end Tunnel type terminal downside for 1 cable(s) 1...16 mm ² flexible without cable end Tunnel type terminal downside for 1 cable(s) 1...16 mm ² flexible with cable end |
| Wire stripping length | 14 mm for bottom connection |
| Tightening torque | 2 N.m bottom |

Environment

| | |
|--|--|
| IP degree of protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution degree | 3 conforming to IEC 60947-2 |
| Electromagnetic compatibility | 8/20 µs impulse withstand, 250 A conforming to IEC 61009-1 |
| Ambient air temperature for operation | -25...60 °C |
| Ambient air temperature for storage | -40...85 °C |

Packing Units

| | |
|-------------------------------------|-------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 165 g |



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No