

# Compact cylinder ADN-S-32-5-I-P

Part number: 8076364

FESTO



## Data sheet

| Feature                                                      | Value                                                                                      |
|--------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Stroke                                                       | 5 mm                                                                                       |
| Piston diameter                                              | 32 mm                                                                                      |
| Cushioning                                                   | Elastic cushioning rings/plates at both ends                                               |
| Mounting position                                            | optional                                                                                   |
| Mode of operation                                            | Double-acting                                                                              |
| Piston-rod end                                               | Female thread                                                                              |
| Design                                                       | Piston<br>Piston rod                                                                       |
| Symbol                                                       | 00991227                                                                                   |
| Variants                                                     | Piston rod at one end                                                                      |
| Operating pressure                                           | 0.06 MPa ... 1 MPa                                                                         |
| Operating pressure                                           | 0.6 bar ... 10 bar                                                                         |
| Operating medium                                             | Compressed air to ISO 8573-1:2010 [7:4:4]                                                  |
| Note on operating and pilot medium                           | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC                               | 1 - Low corrosion stress                                                                   |
| Ambient temperature                                          | 0 °C ... 60 °C                                                                             |
| Impact energy in end positions                               | 0.26 J                                                                                     |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke  | 415 N                                                                                      |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 483 N                                                                                      |
| Moving mass for 0 mm stroke                                  | 31 g                                                                                       |
| Additional moving mass per 10 mm stroke                      | 9 g                                                                                        |
| Basic weight for 0 mm stroke                                 | 107 g                                                                                      |
| Additional weight per 10 mm stroke                           | 36 g                                                                                       |
| Type of mounting                                             | Either:<br>With through-hole<br>Via female thread<br>With accessories                      |
| Pneumatic connection                                         | M5                                                                                         |
| Note on materials                                            | RoHS-compliant                                                                             |
| Material cover                                               | Anodised wrought aluminium alloy                                                           |
| Material dynamic seals                                       | NBR                                                                                        |
| Material housing                                             | Anodised wrought aluminium alloy                                                           |
| Material piston rod                                          | High-alloy stainless steel                                                                 |