



semiconductor relay, 1-pole 3RF3 width 45 mm, 90 A 48-600 V / 4-30 V DC screw terminal blocking voltage 1200 V

|   |  |
|---|--|
| <b>product brand name</b>   | SIRIUS   |
| <b>product designation</b>  | solid-state relay  |
| <b>product type designation</b>   | 3RF30  |
| <b>manufacturer's article number</b>  |  |
| <ul style="list-style-type: none"> <li>_1 of the accessories that can be ordered</li> </ul>   | <a href="#">3RF3900-0WA88</a>                              |
| <b>product designation</b>  |  |
| <ul style="list-style-type: none"> <li>_1 of the accessories that can be ordered</li> </ul>   | heat conducting foil                                       |
| <b>General technical data</b>   |  |
| <b>product function</b>   | zero-point switching                                       |
| <b>power loss [W] for rated value of the current</b>  |  |
| <ul style="list-style-type: none"> <li>at AC in hot operating state</li> <li>at AC in hot operating state per pole</li> <li>without load current share typical</li> </ul> | 47 W<br>47 W<br>0.5 W                                      |
| <b>insulation voltage rated value</b>   | 600 V  |
| surge voltage resistance of main circuit rated value  | 6 kV   |
| <b>protection class IP</b>  | IP20   |
| protection class IP on the front according to IEC 60529   | IP20   |
| <b>shock resistance according to IEC 60068-2-27</b>   | 15g / 11 ms  |
| <b>vibration resistance according to IEC 60068-2-6</b>  | 2g   |
| <b>reference code according to IEC 81346-2</b>  | Q  |
| <b>Substance Prohibitance (Date)</b>  | 01/15/2024   |
| <b>SVHC substance name</b>  | Lead - 7439-92-1<br>Lead monoxide (lead oxide) - 1317-36-8 |
| <b>Net Weight</b>   | 0.08 kg  |
| <b>Main circuit</b>   |  |
| <b>number of poles for main current circuit</b>   | 1  |
| <b>number of NO contacts for main contacts</b>  | 1  |
| <b>number of NC contacts for main contacts</b>  | 0  |
| <b>type of voltage of the operating voltage</b>   | AC   |
| <b>operating voltage</b>  |  |
| <ul style="list-style-type: none"> <li>at AC <ul style="list-style-type: none"> <li>at 50 Hz rated value</li> <li>at 60 Hz rated value</li> </ul> </li> </ul>             | 48 ... 600 V<br>48 ... 600 V                               |
| <b>operating frequency rated value</b>  | 50 ... 60 Hz   |
| <b>relative symmetrical tolerance of the operating frequency</b>  | 10 %   |
| <b>operating range relative to the operating voltage at AC</b>  |  |
| <ul style="list-style-type: none"> <li>at 50 Hz</li> <li>at 60 Hz</li> </ul>  | 40 ... 660 V<br>40 ... 660 V                               |
| <b>operational current rated value maximum</b>  | 50 A   |

|  |  |
|--|--|
| <b>operational current</b>   |  |
| <ul style="list-style-type: none"> <li>• at AC-1 at 400 V rated value</li> <li>• at AC-51 rated value</li> <li>• at AC-51 according to IEC 60947-4-3</li> <li>• according to UL 508 rated value</li> </ul>   | 50 A<br>50 A<br>50 A<br>50 A   |
| <b>rate of voltage rise at the thyristor for main contacts maximum permissible</b>   | 1 000 V/μs   |
| <b>blocking voltage at the thyristor for main contacts maximum permissible</b>   | 1 200 V  |
| <b>reverse current of the thyristor</b>  | 10 mA  |
| <b>derating temperature</b>  | 40 °C  |
| <b>surge current resistance rated value</b>  | 1 300 A  |
| <b>I<sup>2</sup>t value maximum</b>  | 8 000 A <sup>2</sup> ·s  |
| <b>Control circuit/ Control</b>  |  |
| <b>type of voltage of the control supply voltage</b>   | DC   |
| <b>control supply voltage at DC</b>  | 4 ... 30 V   |
| <b>control supply voltage 1 at DC</b>  | 4 ... 30 V   |
| <b>control supply voltage</b>  |  |
| <ul style="list-style-type: none"> <li>• at DC initial value for signal &lt;1&gt; detection</li> <li>• at DC full-scale value for signal&lt;0&gt; recognition</li> </ul>   | 4 V<br>1 V   |
| <b>operating range factor control supply voltage rated value at DC</b>   |  |
| <ul style="list-style-type: none"> <li>• initial value</li> <li>• full-scale value</li> </ul>  | 0.17<br>1.25   |
| <b>control current at minimum control supply voltage</b>   |  |
| <ul style="list-style-type: none"> <li>• at DC</li> </ul>  | 13 mA  |
| control current at DC rated value  | 15 mA  |
| <b>ON-delay time</b>   | 1 ms; additionally max. one half-wave  |
| <b>OFF-delay time</b>  | 1 ms; additionally max. one half-wave  |
| <b>Auxiliary circuit</b>   |  |
| number of CO contacts for auxiliary contacts   | 0  |
| <b>Installation/ mounting/ dimensions</b>  |  |
| fastening method side-by-side mounting   | Yes  |
| <b>fastening method</b>  | screw fixing   |
| <b>design of the thread of the screw for securing the equipment</b>  | M4   |
| <b>tightening torque of fixing screw maximum</b>   | 1.5 N·m  |
| <b>tightening torque [lbf·in] of fixing screw maximum</b>  | 13 lbf·in  |
| <b>height</b>  | 58 mm  |
| <b>width</b>   | 45 mm  |
| <b>depth</b>   | 48 mm  |
| <b>Connections/ Terminals</b>  |  |
| <b>product component removable terminal for auxiliary and control circuit</b>  | Yes  |
| <b>type of electrical connection</b>   |  |
| <ul style="list-style-type: none"> <li>• for main current circuit</li> <li>• for auxiliary and control circuit</li> </ul>  | screw-type terminals<br>screw-type terminals   |
| <b>type of connectable conductor cross-sections</b>  |  |
| <ul style="list-style-type: none"> <li>• for main contacts <ul style="list-style-type: none"> <li>— solid</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>• for AWG cables for main contacts</li> </ul>                             | 2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6 mm <sup>2</sup> )<br>2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6 mm <sup>2</sup> ), 1x 10 mm <sup>2</sup><br>2x (14 ... 10)                                  |
| <b>connectable conductor cross-section for main contacts</b>   |  |
| <ul style="list-style-type: none"> <li>• solid or stranded</li> <li>• finely stranded with core end processing</li> </ul>  | 1.5 ... 6 mm <sup>2</sup><br>1 ... 10 mm <sup>2</sup>  |
| <b>type of connectable conductor cross-sections</b>  |  |
| <ul style="list-style-type: none"> <li>• for auxiliary and control contacts <ul style="list-style-type: none"> <li>— solid</li> <li>— finely stranded with core end processing</li> <li>— finely stranded without core end processing</li> </ul> </li> </ul> | 1x (0.5 ... 2.5 mm <sup>2</sup> ), 2x (0.5 ... 1 mm <sup>2</sup> )<br>1x (0.5 ... 2.5 mm <sup>2</sup> ), 2x (0.5 ... 1 mm <sup>2</sup> )<br>1x (0.5 ... 2.5 mm <sup>2</sup> ), 2x (0.5 ... 1 mm <sup>2</sup> ) |

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>for AWG cables for auxiliary and control contacts</li> </ul>   | 1x (20 ... 12)  |
| <b>AWG number as coded connectable conductor cross section for main contacts</b>  | 14 ... 8  |
| <b>tightening torque</b>  |   |
| <ul style="list-style-type: none"> <li>for main contacts with screw-type terminals</li> </ul>   | 2 ... 2.5 N·m   |
| <ul style="list-style-type: none"> <li>for auxiliary and control contacts with screw-type terminals</li> </ul>                                | 0.5 ... 0.6 N·m   |
| <b>tightening torque [lbf·in]</b>   |   |
| <ul style="list-style-type: none"> <li>for main contacts with screw-type terminals</li> </ul>   | 18 ... 22 lbf·in  |
| <ul style="list-style-type: none"> <li>for auxiliary and control contacts with screw-type terminals</li> </ul>                                | 4.5 ... 5.3 lbf·in  |
| <b>design of the thread of the connection screw</b>   |   |
| <ul style="list-style-type: none"> <li>for main contacts</li> </ul>   | M4  |
| <ul style="list-style-type: none"> <li>of the auxiliary and control contacts</li> </ul>   | M3  |
| <b>stripped length of the cable</b>   |   |
| <ul style="list-style-type: none"> <li>for main contacts</li> </ul>   | 10 mm   |
| <ul style="list-style-type: none"> <li>for auxiliary and control contacts</li> </ul>  | 7 mm  |
| <b>Electrical Safety</b>  |   |
| <b>protection class IP on the front according to IEC 60529</b>  | IP20  |
| <b>touch protection on the front according to IEC 60529</b>   | finger-safe, for vertical contact from the front  |
| <b>Ambient conditions</b>   |   |
| installation altitude at height above sea level maximum   | 1 000 m   |
| <b>ambient temperature</b>  |   |
| <ul style="list-style-type: none"> <li>during operation</li> </ul>  | -25 ... +60 °C  |
| <ul style="list-style-type: none"> <li>during storage</li> </ul>  | -55 ... +80 °C  |
| <b>Electromagnetic compatibility</b>  |   |
| <b>conducted interference</b>   |   |
| <ul style="list-style-type: none"> <li>due to burst according to IEC 61000-4-4</li> </ul>   | 2 kV / 5 kHz behavior criterion 2   |
| <ul style="list-style-type: none"> <li>due to conductor-earth surge according to IEC 61000-4-5</li> </ul>                                     | 2 kV behavior criterion 2   |
| <ul style="list-style-type: none"> <li>due to conductor-conductor surge according to IEC 61000-4-5</li> </ul>                                 | 1 kV behavior criterion 2   |
| <ul style="list-style-type: none"> <li>due to high-frequency radiation according to IEC 61000-4-6</li> </ul>                                  | 140 dBuV in the frequency range 0.15 ... 80 MHz, behavior criterion 1                             |
| <b>field-based interference according to IEC 61000-4-3</b>  | 80 MHz ... 1 GHz 10 V/m, behavior criterion 1   |
| <b>electrostatic discharge according to IEC 61000-4-2</b>   | 4 kV contact discharging / 8 kV air discharging, behavior criterion 2                             |
| <b>conducted HF interference emissions according to CISPR11</b>   | Class A for industrial environment  |
| <b>field-bound HF interference emission according to CISPR11</b>  | Class B for the domestic, business and commercial environments                                    |
| <b>Short-circuit protection, design of the fuse link</b>  |   |
| manufacturer's article number   |   |
| <ul style="list-style-type: none"> <li>of gS fuse for semiconductor protection at NH design usable</li> </ul>                                 | <a href="#">3NE1818-0; These fuses have a smaller rated current than the semiconductor relays</a> |
| <ul style="list-style-type: none"> <li>of back-up R fuse link for semiconductor protection at NH design usable</li> </ul>                     | <a href="#">3NE8021-1</a>   |
| <ul style="list-style-type: none"> <li>of back-up R fuse link for semiconductor protection at cylindrical design 22 x 58 mm usable</li> </ul> | <a href="#">3NC2280; These fuses have a smaller rated current than the semiconductor relays</a>   |
| manufacturer's article number of the gG fuse  |   |
| <ul style="list-style-type: none"> <li>at NH design usable</li> </ul>   | <a href="#">3NA6812-6; These fuses have a smaller rated current than the semiconductor relays</a> |

last modified:

12/7/2025 