


Product datasheet

Specifications

LINERGY BS 4P MULTISTAGE BB 400A 52HOLES



04054

⚠ Discontinued on: 23 Sept 2025

⚠ Discontinued

Main

Range	Linergy
Range of product	Linergy
Product or component type	Multi-stage distribution block
Product name	Linergy BS
Range compatibility	Prisma Prisma G enclosure Prisma Prisma P enclosure
Product compatibility	Spacial enclosures
IP degree of protection	IPxx B

Complementary

Mounting support	Prisma upright Plain backplate Slotted backplate
Mounting mode	Horizontal Vertical
Poles description	4P
[Ue] rated operational voltage	440 V AC
[Ui] rated insulation voltage	750 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	400 A
[In] rated current	400 A at 40 °C
[Icw] rated short-time withstand current	20 kA for 1 s
[Ipk] rated peak withstand current	40 kA
I ² t on activation	400000000 A ² .s
Busbar cross section	32 x 5 mm
Connections - terminals	Supply: crimped lug50 mm ² Supply: flexible bars, 32 x 5 mm Distribution: M6 holes (phase) , 13 x 1...50 mm ²
Height	235 mm
Width	470 mm
Depth	115 mm
Net weight	4.2 kg

Environment

Standards	IEC 61439-2 EN/IEC 61439-1
-----------	-------------------------------

Product certifications	ASEFA
------------------------	-------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	15.5 cm
------------------	---------

Package 1 Width	25.5 cm
-----------------	---------

Package 1 Length	55 cm
------------------	-------

Package 1 Weight	4.11 kg
------------------	---------

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Packaging

EU RoHS Directive	Compliant
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes

Use Longer

Lifetime extension

Repair	No
--------	----

Use Again

Repack and remanufacture

Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins