


Photoelectric Sensors

18 mm Tubular


Accessories, Replacements




Photoelectric Sensors



XUZA218




XSZB118




9006PA18




XUZA118



XUBZ01



XUBZ02



XUZB2003, XUZA0001, XUZA0002

Accessories

Description	Catalog Number
Plastic swivel ball mounting bracket (18 mm)	XUZA218
Plastic mounting bracket	XSZB118
Metal 90° mounting bracket	9006PA18
Zinc diecast 90° mounting bracket	XUZA118
Plastic mounting nuts	XSZE218
Stainless steel mounting nuts	XSZE318
90° mirror adapter for side sensing (Thru-beam only) Decreases sensing distance by 20% (0.80)	Classic type only XUBZ02
90° mirror adapter for side sensing (All other models) Decreases sensing distance by 20% (0.80)	Classic type only XUBZ01
3-D Mounting base	XUZ2003
M12 Stem (75 mm usable length)	XUZ2001
3-D Mounting bracket (stem not included)	XUZB2003

Thru-Beam Emitter and Receiver Replacements

Description	For Replacement of Emitter/Receiver Pair	Catalog Number	Description
Classic Metal AC/DC, Dark Operate	XU2M18MA230	XU2M18MC230T XU2M18MA230R	Emitter Only Receiver Only
Classic Metal AC/DC, Light Operate	XU2M18MB230	XU2M18MC230T XU2M18MB230R	Emitter Only Receiver Only
Classic Metal AC/DC Dark Operate, Micro Connector	XU2M18MA230K	XU2M18MC230KT XU2M18MA230KR	Emitter Only Receiver Only
Classic Metal AC/DC Light Operate, Micro Connector	XU2M18MB230K	XU2M18MC230KT XU2M18MB230KR	Emitter Only Receiver Only
Classic Metal AC/DC Dark Operate, 5 Meter Cable	XU2M18MA230L5	XU2M18MC230L5T XU2M18MA230L5R	Emitter Only Receiver Only
Classic Metal AC/DC Light Operate, 5 Meter Cable	XU2M18MB230L5	XU2M18MC230L5T XU2M18MB230L5R	Emitter Only Receiver Only
Classic Metal DC, NPN Light/Dark Operate	XU2M18NP340	XU2M18KP340T XU2M18NP340R	Emitter Only Receiver Only
Classic Metal DC, NPN Light/Dark Operate, Micro Connector	XU2M18NP340D	XU2M18KP340DT XU2M18NP340DR	Emitter Only Receiver Only
Classic Metal DC, NPN Light/Dark Operate, 5 Meter Connector	XU2M18NP340L5	XU2M18KP340L5T XU2M18NP340L5R	Emitter Only Receiver Only
Classic Metal DC, PNP Light/Dark Operate	XU2M18PP340	XU2M18KP340T XU2M18PP340R	Emitter Only Receiver Only
Classic Metal DC, PNP Light/Dark Operate, Micro Connector	XU2M18PP340D	XU2M18KP340DT XU2M18PP340DR	Emitter Only Receiver Only
Classic Metal DC, PNP Light/Dark Operate, 5 Meter Connector	XU2M18PP340L5	XU2M18KP340L5T XU2M18PP340L5R	Emitter Only Receiver Only
Classic Plastic DC NPN Light/Dark Operate	XU2B18NP340	XU2B18KP340T XU2B18NP340R	Emitter Only Receiver Only
Classic Plastic DC NPN Light/Dark Operate, Micro Connector	XU2B18NP340D	XU2B18KP340DT XU2B18NP340DR	Emitter Only Receiver Only
Classic Plastic DC PNP Light/Dark Operate	XU2B18PP340	XU2B18KP340T XU2B18PP340R	Emitter Only Receiver Only
Classic Plastic DC PNP Light/Dark Operate, Micro Connector	XU2B18PP340D	XU2B18KP340DT XU2B18PP340DR	Emitter Only Receiver Only
Laser Light/Dark Operate, NPN	XU2P18NP340DL	XU2P18KP340DLT XU2P18NP340DLR	Emitter Only Receiver Only
Laser Light/Dark Operate, PNP	XU2P18PP340DL	XU2P18KP340DLT XU2P18PP340DLR	Emitter Only Receiver Only