

# Product datasheet

Specifications



## circuit breaker Compact NSX100HB2 - Micrologic 6.2 E-M - 25 A - 3 poles 3d

LV433345

⚠ Discontinued on: 31 Dec 2022

⚠ Discontinued

### Main

|                                                      |                                                                                                                                                                                         |
|------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                                | ComPact                                                                                                                                                                                 |
| Product name                                         | ComPact NSX                                                                                                                                                                             |
| Range of product                                     | ComPact NSX100...250                                                                                                                                                                    |
| Device short name                                    | NSX100HB2                                                                                                                                                                               |
| Product or component type                            | Circuit breaker                                                                                                                                                                         |
| Device application                                   | Motor                                                                                                                                                                                   |
| Number of poles                                      | 3P                                                                                                                                                                                      |
| Protected poles description                          | 3t                                                                                                                                                                                      |
| [In] rated current                                   | 25 A at 65 °C                                                                                                                                                                           |
| [Ue] rated operational voltage                       | 690 V AC 50/60 Hz                                                                                                                                                                       |
| Network type                                         | AC                                                                                                                                                                                      |
| Network frequency                                    | 50/60 Hz                                                                                                                                                                                |
| Suitability for isolation                            | Yes conforming to EN/IEC 60947-2                                                                                                                                                        |
| Utilisation category                                 | Category A                                                                                                                                                                              |
| [Icu] rated ultimate short-circuit breaking capacity | 100 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level                                    | HB2 100 kA 690 V AC                                                                                                                                                                     |
| Trip unit name                                       | MicroLogic 6.2 E-M                                                                                                                                                                      |
| Trip unit technology                                 | Electronic                                                                                                                                                                              |
| Trip unit protection functions                       | LSIG                                                                                                                                                                                    |
| Control type                                         | Toggle                                                                                                                                                                                  |
| Circuit breaker mounting mode                        | Fixed                                                                                                                                                                                   |

### Complementary

|                                                     |                                                                                                                                                                             |
|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ui] rated insulation voltage                       | 800 V AC 50/60 Hz                                                                                                                                                           |
| [Uimp] rated impulse withstand voltage              | 8 kV                                                                                                                                                                        |
| [Ics] rated service short-circuit breaking capacity | 100 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability                               | 50000 cycles                                                                                                                                                                |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical durability                                     | 10000 cycles at 690 V In<br>20000 cycles at 690 V In/2<br>30000 cycles at 440 V In<br>50000 cycles at 440 V In/2                                                                                                                                                                                                                                                                                                                                                |
| Mounting support                                          | Backplate                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Upside connection                                         | Front                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Downside connection                                       | Front                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Connection pitch                                          | 35 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Protection type                                           | L : for overload protection (long time)<br>S : for short time short-circuit protection<br>I : for instantaneous short-circuit protection<br>G : for ground fault protection                                                                                                                                                                                                                                                                                     |
| Trip unit rating                                          | 25 A at 65 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Motor tripping class                                      | 30<br>20<br>10<br>5                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Complementary motor protection                            | Protracted starting time<br>Underload<br>Stalled rotor<br>Phase unbalance                                                                                                                                                                                                                                                                                                                                                                                       |
| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable 9 settings                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| [Ir] long-time protection pick-up adjustment range        | 12...25 A                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Long-time protection delay adjustment type tr             | Adjustable                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| [tr] long-time protection delay adjustment range          | 10 s at 7.2 x Ir for trip class 10<br>120 s at 1.5 x Ir for trip class 5<br>20 s at 7.2 x Ir for trip class 20<br>240 s at 1.5 x Ir for trip class 10<br>26 s at 6 x Ir for trip class 20<br>480 s at 1.5 x Ir for trip class 20<br>5 s at 7.2 x Ir for trip class 5<br>13.5 s at 6 x Ir for trip class 10<br>6.5 s at 6 x Ir for trip class 5<br>30 s at 7.2 x Ir for trip class 30<br>38 s at 6 x Ir for trip class 30<br>720 s at 1.5 x Ir for trip class 30 |
| Thermal memory                                            | 20 minutes before and after tripping                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Short-time protection pick-up adjustment type Isd         | Adjustable                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| [Isd] Short-time protection pick-up adjustment range      | 5...13 x Ir                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Short-time protection delay adjustment type tsd           | Fixed                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Instantaneous protection pick-up adjustment type Ii       | Fixed                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| [Ii] instantaneous protection pick-up adjustment range    | 425 A                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Ground-fault protection pick-up adjustment type Ig        | Adjustable 9 settings                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| [Ig] ground-fault protection pick-up adjustment range     | 0.6...1 x In for In = 25 A<br>0.3...1 x In for In = 50 A<br>0.2...1 x In for In > 50 A<br>Ig enable on/off                                                                                                                                                                                                                                                                                                                                                      |
| Ground-fault protection time delay adjustment type tg     | Adjustable                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| [tg] ground-fault protection time delay adjustment range  | 0...0.4 s                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Earth-leakage protection                                  | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Zone selective interlocking ZSI                           | With                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Number of slots for electrical auxiliaries                | 5 slot(s)                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

|                       |                                                                                                                                                                                                                                                                            |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Local signalling      | Flashing LED (green) for ready to operate<br>LED 95 % lth (red) for temperature over set point                                                                                                                                                                             |
| Display type          | LCD display                                                                                                                                                                                                                                                                |
| Type of measurement   | Energy meter                                                                                                                                                                                                                                                               |
| Communication of data | Instantaneous and demand values<br>Phase sequence<br>Power quality<br>Maintenance indicators<br>Energy metering<br>Protection and alarm settings<br>Demand current and power<br>Thermal image function<br>Time-stamped histories and event tables<br>Maximeters/minimeters |
| Width (W)             | 105 mm                                                                                                                                                                                                                                                                     |
| Height (H)            | 161 mm                                                                                                                                                                                                                                                                     |
| Depth (D)             | 86 mm                                                                                                                                                                                                                                                                      |
| Net weight            | 2.05 kg                                                                                                                                                                                                                                                                    |

## Environment

|                                       |                                                              |
|---------------------------------------|--------------------------------------------------------------|
| Standards                             | EN/IEC 60947                                                 |
| Product certifications                | EAC<br>CCC<br>Marine                                         |
| Overvoltage category                  | Class II                                                     |
| Electrical shock protection class     | Class II                                                     |
| Pollution degree                      | 3 conforming to IEC 60664-1                                  |
| IP degree of protection               | IP40 conforming to IEC 60529                                 |
| IK degree of protection               | IK07 conforming to IEC 62262                                 |
| Ambient air temperature for operation | -25...70 °C                                                  |
| Ambient air temperature for storage   | -40...85 °C                                                  |
| Relative humidity                     | 0...95 %                                                     |
| Operating altitude                    | 0...2000 m without derating<br>2000 m...5000 m with derating |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 13.5 cm |
| Package 1 Width              | 10.8 cm |
| Package 1 Length             | 19.2 cm |
| Package 1 Weight             | 1.94 kg |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

EU RoHS Directive

[Compliant](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins