



Main

Range	TeSys
Device short name	LA9G
Product or Component Type	Connector
Device Application	Control circuit
Range Compatibility	TeSys G
Quantity per Set	Set of 1

Complementary

Maximum Horse Power Rating	600 V AC 50/60 Hz UL 600 V AC 50/60 Hz IEC
[Ie] rated operational current	10 A
Pin number	4
Dielectric test voltage	3000 kV AC, 1 minute
Overvoltage category	III
Connections - terminals	Control circuit push-in 1 0.00...0.00 in ² (0.2...2.5 mm ²) solid stranded without cable end Control circuit push-in 1 0.00...0.00 in ² (0.25...2.5 mm ²) flexible with cable end Control circuit push-in 2 0.00...0.00 in ² (0.5...1.0 mm ²) with cable end
Product Weight	0.11 lb(US) (0.05 kg)
Height	0.59 in (15 mm)
Width	1.02 in (26 mm)
Depth	1.42 in (36 mm)

Environment

IP degree of protection	IP20 conforming to IEC 60529
Pollution degree	3 IEC 60947-1
Standards	EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1 GB/T 14048.5
Ambient Air Temperature for Operation	-13...140 °F (-25...60 °C)
Ambient Air Temperature for Storage	-76...176 °F (-60...80 °C)

Ordering and shipping details

Category	22328-TESYS GIGA ACCESSORIES
Discount Schedule	I12
GTIN	3606481916051
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 in (2.0 cm)
Package 1 Width	2.17 in (5.5 cm)
Package 1 Length	3.15 in (8.0 cm)
Package 1 Weight	0.53 oz (15.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	19.96 oz (566.0 g)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product