

Product data sheet

Specifications



Auxiliary contacts, TeSys GS, 1 NO, early break, for GS1 32 A with direct front handle

GS2AM110

⚠ Discontinued on: Jul 24, 2022

⚠ Discontinued

Main

Range of product	TeSys
Device short name	GS2AM
Product or component type	Auxiliary contact
Contact application	O, I and test position signalling
Contacts type and composition	1 NO
Contact operation	Early-break
[I _{th}] conventional free air thermal current	16 A (at 40 °C)
[I _e] rated operational current	3 A at 240 V AC-15 6 A at 120 V AC-15 1.5 A at 480 V AC-15 1.8 A at 400 V AC-15 2.8 A at 24 V DC-13 0.15 A at 400 V DC-13 0.27 A at 250 V DC-13 0.55 A at 125 V DC-13 1.4 A at 48 V DC-13

Complementary

Mechanical durability	5000000 cycles
Electrical durability	1000000 cycles AC-15
Product compatibility	GS2
switch rated current	1250 A 50 A 200 A 125 A 160 A 400 A 600 A 63 A 800 A 100 A 250 A 32 A 60 A 315 A 630 A
Type of operating handle	External left side External right side External frontal
Net weight	0.015 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No