

Product data sheet

Specifications



ASCO 4100 Load Bank

ASCOLBLV4100

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

Voltage Rating 208 V AC 60 Hz, 3 phase
240/480 V AC 60 Hz, 3 phase
240 V AC 60 Hz, 3 phase
400 V AC 50 Hz, 3 phase
480 V AC 60 Hz, 3 phase
600 V AC 60 Hz, 3 phase

Capacity Rating 50 kW
75 kW
100 kW
125 kW
150 kW

Load Step Resolution 5 kW

Cooling System Rating 2244208.2 Gal/hr(US) (8495.1 m3/h)

Provided Equipment Switch 3 On-Off
LED 2 on
LED 1 alarm indication
Cooling fans 1

Enclosure Material Aluminium
Steel

Surface Finish Polyester powder

Color Gray

Connection Terminals Terminals inside)

Length 48.0 in (1219 mm)

Width 27.0 in (685 mm)

Height 35 in (889 mm)

Product Weight 500.4 lb(US) (227 kg)

Environment

Ambient Air Temperature -18...122 °F (-28...50 °C)

Standards ISO 9001
NEMA
UL 508 A

Packing Units

Unit Type of Package 1 PCE

Nbr. of units in pkg. 1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Height	48.0 in (121.9 cm)
Package 1 Width	27.0 in (68.5 cm)
Package 1 Length	35.0 in (88.9 cm)
Package weight(Lbs)	500.4 lb(US) (227.0 kg)

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	No
--------------------------------------	----

Use Longer



Lifetime extension

Repair	No
--------	----