

Product datasheet

Specifications



low level auxiliary contact, ComPact NS630b to NS3200, fixed, circuit breaker status SDE, 1 changeover contact type

33012

Main

Product or component type	Auxiliary contact
Device short name	SDE
Device application	Breaker status monitoring
Range compatibility	ComPact ComPact NS630b...1600 ComPact ComPact NS1600b...3200
Signal contacts composition	1 NO/NC

Complementary

Fault type	General electric fault
Local signalling	Fault trip for electrical fault
Auxiliary contacts type	Low level
Mounting mode	Clip-on
[Ith] conventional free air thermal current	5 A
Breaking capacity (A)	AC-12: 5 A at 24 V AC 50/60 Hz AC-12: 5 A at 48 V AC 50/60 Hz AC-12: 5 A at 110 V AC 50/60 Hz AC-12: 5 A at 220/240 V AC 50/60 Hz AC-12: 5 A at 380/440 V AC 50/60 Hz AC-12: 5 A at 480 V AC 50/60 Hz AC-15: 3 A at 24 V AC 50/60 Hz AC-15: 3 A at 48 V AC 50/60 Hz AC-15: 2.5 A at 110 V AC 50/60 Hz AC-15: 2 A at 220/240 V AC 50/60 Hz AC-15: 1.5 A at 380/440 V AC 50/60 Hz AC-15: 1 A at 480 V AC 50/60 Hz DC-12: 5 A at 24 V DC 50/60 Hz DC-12: 2.5 A at 48 V DC 50/60 Hz DC-12: 0.6 A at 110 V DC DC-12: 0.3 A at 250 V DC DC-14: 1 A at 24 V DC DC-14: 0.2 A at 48 V DC DC-14: 0.05 A at 110 V DC DC-14: 0.03 A at 250 V DC
Minimum load	1 mA at 4 V DC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	4.0 cm
Package 1 Length	5.0 cm
Package 1 Weight	800.0 g

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins