

# Product datasheet

Specifications



## TeSys F Contactor - 3P (3 NO) - AC1 - <= 1000 V AC 2600 A - coil 220 V AC

LC1F2600M7

⚠ Discontinued on: 23 Jan 2021

⚠ Discontinued

### Main

Range	TeSys
Range of product	TeSys F
Product or component type	Contactor
Device short name	LC1F
Contactor application	Resistive load
Utilisation category	AC-1
Poles description	3P
[Ue] rated operational voltage	<= 1000 V AC 50/60 Hz
[Uc] control circuit voltage	220 V AC 40...400 Hz
[Ie] rated operational current	2600 A (at <60 °C) AC AC-1

### Complementary

[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	2600 A (at 60 °C)
Rated breaking capacity	3900 A conforming to IEC 60947-4-1
[Icw] rated short-time withstand current	12000 A 40 °C - 10 s 9000 A 40 °C - 30 s 7000 A 40 °C - 1 min 6000 A 40 °C - 3 min 4000 A 40 °C - 10 min
Associated fuse rating	2500 A gG at <= 440 V
Average impedance	0.1 mOhm - Ith 2600 A 50 Hz
[Ui] rated insulation voltage	1000 V conforming to IEC 60947-4-1 1000 V conforming to UL 60947-4-1
Power dissipation per pole	250 W AC-1
Overvoltage category	III
power pole contact composition	3 NO
Control circuit voltage limits	Operational: 0.85...1.1 Uc 40...400 Hz (at 55 °C) Drop-out: 0.3...0.5 Uc 40...400 Hz (at 55 °C)
Inrush power in VA	2500 VA, 40...400 Hz cos phi 0.9 (at 20 °C)
Hold-in power consumption in VA	45 VA, 40...400 Hz cos phi 0.9 (at 20 °C)
Maximum operating rate	600 cyc/h 55 °C
Operating time	40...80 ms closing 100...200 ms opening

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

<b>Connections - terminals</b>	Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> solid without cable end Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> solid without cable end Power circuit: bar 3 cable(s) - busbar cross section: 100 x 10 mm
<b>Tightening torque</b>	Control circuit: 1.2 N.m Power circuit: 58 N.m
<b>Mounting support</b>	Plate
<b>Heat dissipation</b>	40 W
<b>Standards</b>	EN 60947-4-1 IEC 60947-1 IEC 60947-4-1 EN 60947-1 JIS C8201-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
<b>Product certifications</b>	CB Scheme CCC CSA UL UKCA EAC
<b>Compatibility code</b>	LC1F
<b>Control circuit type</b>	AC at 40...400 Hz

## Environment

<b>IP degree of protection</b>	IP20 front face with shrouds conforming to IEC 60529 IP20 front face with shrouds conforming to VDE 0106
<b>Protective treatment</b>	TH
<b>Ambient air temperature for operation</b>	-5...40 °C
<b>Ambient air temperature for storage</b>	-60...80 °C
<b>Permissible ambient air temperature around the device</b>	-40...60 °C
<b>Height</b>	382 mm
<b>Width</b>	519 mm
<b>Depth</b>	251 mm
<b>Operating altitude</b>	3000 m without derating
<b>Net weight</b>	36 kg

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	38 cm
<b>Package 1 Width</b>	50 cm
<b>Package 1 Length</b>	60 cm
<b>Package 1 Weight</b>	37 kg

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

EU RoHS Directive

[Compliant](#)

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

End of life manual availability

[End of Life Information](#)

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins