

Product datasheet

Specifications



Plug in relay, Zelio Relay with suppressor, RHN, instantaneous, 4 C/O, 110 V DC, 1 A

RHN422FA76

⚠ Discontinued on: 1 Aug 2022

⚠ Discontinued

Main

Range of product	Harmony Relay
Product or component type	Plug-in relay
Device short name	RHN
Contacts type and composition	4 C/O
Contact operation	Low level Instantaneous
[Uc] control circuit voltage	110 V DC
[Ithe] conventional enclosed thermal current	1 A 40 °C
status LED	Without
Control type	Manual control
Coil interference suppression	With

Complementary

[Ui] rated insulation voltage	250 V
Operating position	Any position
Minimum switching capacity	50 mVA at 1 mA 50 mVA, 1 V
Contact bounce time	<= 10 ms
Maximum voltage drop	<100 V for 3 A at 24 V
Average resistance	30 mOhm at 20 °C
Average coil consumption	1.6 W at 20 °C
Control circuit voltage limits	0.8...1.1 U _c conforming to IEC 60255
Drop-out voltage threshold	0.1...0.3 U _c
Time constant	12 ms for open contact(s) 15 ms for closed contact(s)
Mechanical durability	20000000 cycles
maximum operating rate	6 cyc/mn
Operating time	1...4 ms for energisation/de-energisation 1.2...4 ms for de-energisation/energisation 10...20 ms between energisation of coil and closing of NO contact at 20 °C 2...7 ms between de-energisation of coil and closing of NC contact at 20 °C
CAD overall width	33 mm
CAD overall height	43 mm

CAD overall depth	54 mm
Terminals description ISO n°1	(11-12-14)OC (21-22-24)OC (A1-A2)CO (31-32-34)OC (41-42-44)OC
Net weight	0.09 kg
Compatibility code	RHN

Environment

Standards	VDE 0435 IEC 60255 NF C 45-250 BS 4794
Product certifications	BV UR ASE CSA EDF USSR
Protective treatment	TC
Dielectric strength	2500 V
Ambient air temperature for operation	-5...40 °C conforming to IEC 60255
Ambient air temperature for storage	-40...70 °C
Vibration resistance	6 gn (f= 10...55 Hz) conforming to IEC 60068-2-6 6 gn (f= 10...55 Hz) conforming to NF C 20-616
Shock resistance	50 gn for 11 ms conforming to NF C 20-608

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	5 cm
Package 1 Length	7.8 cm
Package 1 Weight	92 g

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant](#)

Use Longer



Lifetime extension

Repair

No