


Product datasheet

Specifications



Analog input card, Harmony iPC, Interface M.2 2x 0 10V/4 20 mA for HMIBSC

HMIYBIN2AIM21

⚠ Discontinued on: 23 Jan 2021

⚠ End-of-service on: 30 Jun 2023

⚠ Discontinued

Main

Range of product	Harmony iPC
Product or component type	Analog input card
Accessory / separate part category	Connection accessory

Complementary

Accessory / separate part destination	HMIBSC modular IIoT box core
Integrated connection type	M.2 Auto calibration screw terminals, transmission rate: 16 bits resolution analogue cableAccuracy $\pm 0.2\%$ M.2 screw terminals
Range compatibility	Harmony iPC

Environment

Ambient air temperature for operation	0...50 °C HMIBSC
---------------------------------------	------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	14 cm
Package 1 Length	16 cm
Package 1 Weight	100 g
Unit Type of Package 2	BB1
Number of Units in Package 2	1
Package 2 Height	5.4 cm
Package 2 Width	13.8 cm
Package 2 Length	16 cm
Package 2 Weight	200 g
Unit Type of Package 3	S02
Number of Units in Package 3	4
Package 3 Height	15 cm
Package 3 Width	30 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 3 Length	40 cm
Package 3 Weight	686 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

SCIP Number

385c5f7a-4cc2-42bf-8ac5-005c2900f2ce

Use Longer



Lifetime extension

Repair

No