

Product datasheet

Specifications

Motors



AC servo motor BDH - 0.87 N.m - 8000 rpm - untapped shaft - without brake - IP54

BDH0582E05A2A

⚠ Discontinued on: 8 Jul 2022

⚠ Discontinued

EAN Code: 3389118169906

Main

Product or component type	AC servo motors
Component name	BDH
Continuous stall torque	0.87 N.m for LXM15LD13M3 3 phases 0.87 N.m for LXM15LD13M3 single phase
Peak stall torque	2.42 N.m for LXM15LD13M3 at 230 V 3 phases 2.42 N.m for LXM15LD13M3 at 230 V single phase
Nominal output power	500 W for LXM15LD13M3 at 230 V 3 phases 500 W for LXM15LD13M3 at 230 V single phase
Nominal torque	0.71 N.m for LXM15LD13M3 at 230 V 3 phases 0.71 N.m for LXM15LD13M3 at 230 V single phase
Nominal speed	6500 rpm for LXM15LD13M3 at 230 V 3 phases 6500 rpm for LXM15LD13M3 at 230 V single phase
Maximum mechanical speed	8000 rpm
Product compatibility	LXM15LD13M3 at 230 V 3 phases LXM15LD13M3 at 230 V single phase
Shaft end	Untapped
IP degree of protection	IP54
Encoder type	2-pole resolver
Speed feedback resolution	65536 points/turn
Holding brake	Without
Mounting support	International IEC standard flange
Electrical connection	Rotatable right-angled connectors
Number of poles	6

Complementary

Range compatibility	Lexium 15
Maximum current Irms	7.7 A
Torque constant	0.32 N.m/A at 120 °C
Back emf constant	20.4 V/krpm at 120 °C
Stator resistance	5.09 Ohm at 20 °C
Stator inductance	9.7 mH at 20 °C
Stator electrical time constant	1.91 ms at 20 °C

Maximum radial force Fr	127 N at 8000 rpm
	128 N at 7000 rpm
	130 N at 6000 rpm
	132 N at 5000 rpm
	133 N at 4000 rpm
	135 N at 3000 rpm
	137 N at 2000 rpm
138 N at 1000 rpm	

Maximum axial force Fa	0.3 x Fr
-------------------------------	----------

Net weight	1.1 kg
-------------------	--------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No