


# Product datasheet

Specifications



reversing Contactor, TeSys K, 3P,  
AC-3/AC-3e,440V 6A, 1NC, 230V  
AC coil,with integral suppression  
device

LC2K0601P72

## Main

Range	TeSys
Product name	TeSys K
Product or component type	Reversing contactor
Device short name	LC2K
Device application	Control
Contactor application	Motor control
Utilisation category	AC-4 AC-3 AC-3e
Device presentation	Preassembled with reversing power busbar
Poles description	3P
power pole contact composition	3 NO
[Ue] rated operational voltage	Power circuit: 690 V AC 50/60 Hz Signalling circuit: <= 690 V AC 50/60 Hz
[Ie] rated operational current	6 A at <= 440 V AC AC-3 for power circuit 6 A at <= 440 V AC AC-3e for power circuit
Motor power kW	1.5 kW at 220...230 V AC 50/60 Hz 2.2 kW at 380...415 V AC 50/60 Hz 3 kW at 440 V AC 50/60 Hz 3 kW at 480 V AC 50/60 Hz 3 kW at 500...600 V AC 50/60 Hz 3 kW at 660...690 V AC 50/60 Hz
Control circuit type	AC at 50/60 Hz
[Uc] control circuit voltage	230 V AC 50/60 Hz
Auxiliary contact composition	1 NC
[Uimp] rated impulse withstand voltage	8 kV
Oversvoltage category	III
[Ith] conventional free air thermal current	20 A (at 50 °C) for power circuit 10 A (at 50 °C) for signalling circuit
Irms rated making capacity	110 A AC for power circuit conforming to NF C 63-110 110 A AC for power circuit conforming to IEC 60947 110 A AC for signalling circuit conforming to IEC 60947
Rated breaking capacity	110 A at 415 V conforming to IEC 60947 110 A at 440 V conforming to IEC 60947 80 A at 500 V conforming to IEC 60947 110 A at 220...230 V conforming to IEC 60947 110 A at 380...400 V conforming to IEC 60947 70 A at 660...690 V conforming to IEC 60947

Excluding VAT, FCA Jabal Ali & amp; are subject to change – check with your local distributor.

<b>[Icw] rated short-time withstand current</b>	<p>90 A 50 °C - 1 s for power circuit  85 A 50 °C - 5 s for power circuit  80 A 50 °C - 10 s for power circuit  60 A 50 °C - 30 s for power circuit  45 A 50 °C - 1 min for power circuit  40 A 50 °C - 3 min for power circuit  80 A - 1 s for signalling circuit  90 A - 500 ms for signalling circuit  110 A - 100 ms for signalling circuit  20 A 50 °C - &gt;= 15 min for power circuit</p>
<b>Associated fuse rating</b>	<p>25 A gG at &lt;= 440 V for power circuit  25 A aM for power circuit  10 A gG for signalling circuit conforming to IEC 60947  10 A gG for signalling circuit conforming to VDE 0660</p>
<b>Average impedance</b>	3 mOhm - lth 20 A 50 Hz for power circuit
<b>[Ui] rated insulation voltage</b>	<p>Power circuit: 600 V conforming to UL 508  Power circuit: 690 V conforming to IEC 60947-4-1  Signalling circuit: 690 V conforming to IEC 60947-4-1  Signalling circuit: 690 V conforming to IEC 60947-5-1  Signalling circuit: 600 V conforming to UL 508  Power circuit: 600 V conforming to CSA C22.2 No 14  Signalling circuit: 600 V conforming to CSA C22.2 No 14</p>
<b>Electrical durability</b>	<p>1.3 Mcycles 6 A AC-3 at Ue &lt;= 440 V  1.3 Mcycles 6 A AC-3e at Ue &lt;= 440 V  0.05 Mcycles 36 A AC-4 at Ue &lt;= 440 V</p>
<b>Interlocking type</b>	Mechanical
<b>Mounting support</b>	<p>Rail  Plate</p>
<b>Standards</b>	<p>EN/IEC 60947-4-1  GB/T 14048.4  UL 60947-4-1  CSA C22.2 No 60947-4-1  JIS C8201-4-1</p>
<b>Product certifications</b>	<p>CB Scheme  CCC  UL  CSA  EAC  CE  UKCA</p>
<b>Connections - terminals</b>	<p>Screw clamp terminals 1 cable(s) 1.5...4 mm<sup>2</sup>solid  Screw clamp terminals 1 cable(s) 0.75...4 mm<sup>2</sup>flexible without cable end  Screw clamp terminals 1 cable(s) 0.34...2.5 mm<sup>2</sup>flexible with cable end  Screw clamp terminals 2 cable(s) 1.5...4 mm<sup>2</sup>solid  Screw clamp terminals 2 cable(s) 0.75...4 mm<sup>2</sup>flexible without cable end  Screw clamp terminals 2 cable(s) 0.34...1.5 mm<sup>2</sup>flexible with cable end</p>
<b>Tightening torque</b>	<p>0.8...1.3 N.m - on screw clamp terminals Philips No 2  0.8...1.3 N.m - on screw clamp terminals flat Ø 6 mm  0.8...1.3 N.m - on screw clamp terminals pozidriv No 2</p>
<b>Operating time</b>	<p>10...20 ms coil energisation and NO closing  10...20 ms coil de-energisation and NO opening</p>
<b>Safety reliability level</b>	<p>B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1  B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1</p>
<b>Mechanical durability</b>	5 Mcycles
<b>Maximum operating rate</b>	3600 cyc/h

## Complementary

<b>Coil technology</b>	Built-in bidirectional peak limiting diode suppressor
<b>Control circuit voltage limits</b>	<p>Operational: 0.8...1.15 Uc (at &lt;50 °C)  Drop-out: 0.2...0.75 Uc (at &lt;50 °C)</p>

Inrush power in VA	30 VA (at 20 °C)
Hold-in power consumption in VA	4.5 VA (at 20 °C)
Heat dissipation	1.3 W
Auxiliary contacts type	type instantaneous 1 NC
Signalling circuit frequency	<= 400 Hz
Minimum switching current	5 mA for signalling circuit
Minimum switching voltage	17 V for signalling circuit
Non overlap distance	0.5 mm
Insulation resistance	> 10 MOhm for signalling circuit

## Environment

IP degree of protection	IP20 conforming to VDE 0106
Protective treatment	TC conforming to IEC 60068 TC conforming to DIN 50016
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-50...80 °C
Operating altitude	2000 m without derating
Flame retardance	V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102
Mechanical robustness	Shocks contactor closed, on X axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed, on Y axis: 15 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed, on Z axis: 15 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on X axis: 6 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on Y axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on Z axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Vibrations contactor closed: 4 Gn, 5...300 Hz conforming to IEC 60068-2-6 Vibrations contactor opened: 2 Gn, 5...300 Hz conforming to IEC 60068-2-6
Height	58 mm
Width	90 mm
Depth	57 mm
Net weight	0.39 kg

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.200 cm
Package 1 Width	6.800 cm
Package 1 Length	9.300 cm
Package 1 Weight	366.000 g

## Contractual warranty

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	101 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	98 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.6 kg CO2 eq.

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	<a href="#">Compliant</a>
REACH Regulation	<a href="#">Free of Substances of Very High Concern above the threshold</a>

## Use Longer




### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	64
End of life manual availability	<a href="#">End of Life Information</a>
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Offer Marketing Illustration

Product benefits / Features

---

## TeSys K Technical Benefits



- Preassembled with reversing power busbar
- Built-in in all 3 pole versions: 1NO or 1NC
- Up to 4 more by add-on blocks
- Wide variety of coil voltage and terminal connection options
- Delivers strong performance for its compact size and promises seamless integration in all applications and use
- Pre-wired power circuit connections as standard on screw clamp versions.
- It Features specific versions for railway (TeSys S207) and electrodomestic (TeSys S335) applications

Offer Marketing Illustration

Product benefits / Features

---

## TeSys K

### Reversing contactors



#### Flexibility

Designed with control voltages, low consumption, minimal noise levels, robust power connections, and a range of auxiliaries, and application-specific variants to meet diverse needs.



#### Safety

It provide ultimate protection with IP20 finger-safe terminals, built-in NO/NC auxiliary contacts, and IEC-certified mirror and mechanically linked contacts for safety applications.



#### Compact size

Up to 50% less volume is captured in your panels. One of the smallest contactors offerings in the market



Technical Illustration

Assembly's dimensions

---

